

INDUSTRIAL COMPONENT DATA

DE1-341D3NN-N20N 177365 Y7-177365 EATON ELECTRIC

Variable speed starter, Rated operational voltage 400 V AC,...

Brand: EATON - MOELLER | Manufacturer Part Number: DE1-341D3NN-N20N



Manufacturer	EATON - MOELLER
MPN / Reference	DE1-341D3NN-N20N
Catalog number	Y7-177365
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-F571E82F95
Generated	2026-08-02

Product Overview

Variable speed starter, Rated operational voltage 400 V AC, 3-phase, Ie 1.3 A, 0.37 kW, 0.5 HP
DE1-341D3NN-N20N

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Power XL Frequency Converters

Additional Product Information

General specifications

Product Name Eaton DE1 Variable speed starter Catalog Number 177365 Model Code DE1-341D3NN-N20N EAN 4015081718252 Product Length/Depth 169 mm Product Height 230 mm Product Width 45 mm Product Weight 1 kg

Certifications Safety requirements: IEC/EN 61800-5-1

UL File No.: E172143

UL report applies to both US and Canada

IEC/EN61800-5

UL Category Control No.: NMMS, NMMS7

UL 508C

IEC/EN61800-3

CUL

Certified by UL for use in Canada

CSA-C22.2 No. 14

Specification for general requirements: IEC/EN 61800-2

UL
CE
RCM
RoHS, ISO 9001
IEC/EN 61800-3 Catalog Notes Overload cycle for 60 s every 600 s Features & Functions
Features Parameterization: drivesConnect
Parameterization: drivesConnect mobile (App)
Parameterization: Fieldbus
Parameterization: Keypad Fitted with: PC connection General
Cable length C2 <= 10 m, Radio interference level, maximum motor cable length
C3 <= 25 m, Radio interference level, maximum motor cable length Communication interface Modbus RTU, built in
OP-Bus (RS485), built in Connection to SmartWire-DT In conjunction with DX-NET-SWD3 SmartWire DT module
Yes Degree of protection IP20
NEMA Other Electromagnetic compatibility 1st and 2nd environments (according to EN 61800-3) Frame size FS1 Product
category Variable speed starter Protection Finger and back-of-hand proof, Protection against direct contact (BGV A3,
VBG4) Protocol MODBUS
EtherNet/IP
Other bus systems Radio interference class C2, C3: depending on the motor cable length, the connected loa...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DE1-341D3NN-N20N with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.