

INDUSTRIAL COMPONENT DATA

DG1-32061FN-C21C 9701-4004-00P Y7-9701-4004-00P EATON ELECTRIC DG1-32061FN-C21C Variable frequency drive, 3-..

Brand: EATON - MOELLER | Manufacturer Part Number: DG1-32061FN-C21C



Manufacturer	EATON - MOELLER
MPN / Reference	DG1-32061FN-C21C
Catalog number	Y7-9701-4004-00P
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-E745121187
Generated	2026-08-05

Product Overview

DG1-32061FN-C21C Variable frequency drive, 3-phase 240 V, 61A, EMC filter, degree of protection IP21

DG1-32061FN-C21C

Eaton DG1 Variable frequency drive, 230 V AC, 3-phase, 61 A, 15 kW, IP21/NEMA1, DC link choke

Variable frequency drive, Part group reference (e.g. DIL): DG1, Rated operational voltage: $U_e = 230 \text{ V AC}$, 3-phase, 240 V AC, 3-phase, Output voltage with V_e : $U_2 = 230 \text{ V AC}$, 3-phase, 240 V AC, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 208 (-15\%) - 240 (+10\%) \text{ V}$, Rated operational current At 150% overload: $I_e = 61 \text{ A}$, Note: Rated operational current for a switching frequency of 1 - 10 kHz and an ambient temperature of +50 °C for a 150% overload and +40 °C for a 110% overload, Rated operational current At 110% overload: $I_e = 75 \text{ A}$, Note: Overload cycle for 60 s every 600 s , Assigned motor rating Note: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm-1 at 50 Hz or 1800 min-1 at 60 Hz, Overload cycle for 60 s every 600 s, at 230 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 15 \text{ kW}$, 110 % Overload: $P = 22 \text{ kW}$, 150 % Overload: $I_M = 51 \text{ A}$, 110 % Overload: $I_M = 71 \text{ A}$, Assigned motor rating Note: at 230 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 20 \text{ HP}$, 110 % Overload: $P = 25 \text{ HP}$, Assigned motor rating 150 % Overload: $I_M = 54 \text{ A}$, 110 % Overload: $I_M = 68 \text{ A}$, Degree of Protection: IP21/NEMA1, Interface/field bus (built-in): M...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Power XL Frequency Converters**

Additional Product Information

General specifications

Product Name Eaton DG1 variable frequency drive Catalog Number 9701-4004-00P Model Code DG1-32061FN-C21C

EAN 4015081734122 Product Length/Depth 294 mm Product Height 630 mm Product Width 237.7 mm Product Weight 34 kg Certifications UL

EAC

Safety requirements: IEC/EN 61800-5

CE

Specification for general requirements: IEC/EN 61800-2

UL File No.: E134360

CUL

IEC/EN61800-5

UkrSEPRO

C-Tick

UL508

Certified by UL for use in Canada

UL Category Control No.: NMMS, NMMS7

IEC/EN 61800-3

IEC/EN61800-3

RoHS, ISO 9001

CSA-C22.2 No. 274-13

UL report applies to both US and Canada Features & Functions

Features Temperature-controlled fan

Externally accessible fan

Parameterization: Fieldbus

Parameterization: Keypad

Parameterization: Power Xpert inControl General

Air volume capacity 260 m³/h Cable length C2 ≤ 10 m, Radio interference level, maximum motor cable length

C3 ≤ 50 m, Radio interference level, maximum motor cable length

200 m, screened, maximum permissible, Motor feeder Degree of protection IP21

NEMA 1 Electromagnetic compatibility 1st and 2nd environments (according to EN 61800-3) Environmental class 3C2, 3S2

(Air quality) Fitted with: Control unit

Radio interference suppression filter

Multi-line graphic display

Internal DC link

IGBT inverter

DC link choke

Additional PCB protection

PC connection Frame size FS4 Mounting position Vertical Number of slots 2 (expansion) Overvoltage category III Pollution degree 2 Product Category Variable frequency drives Protection...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DG1-32061FN-C21C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.