

INDUSTRIAL COMPONENT DATA

**DG1-324D8FB-C54C 9701-1103-00P Y7-9701-1103-00P EATON
ELECTRIC DG1-324D8FB-C54C Variable frequency drive, 3-..**

Brand: EATON - MOELLER | Manufacturer Part Number: DG1-324D8FB-C54C



Manufacturer	EATON - MOELLER
MPN / Reference	DG1-324D8FB-C54C
Catalog number	Y7-9701-1103-00P
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-B6B38989E6
Generated	2026-08-05

Product Overview

DG1-324D8FB-C54C Variable frequency drive, 3-phase 240 V, 4.8A, EMC filter, Internal braking transistor, protection type IP54

DG1-324D8FB-C54C

Eaton DG1 Variable frequency drive, 230 V AC, 3-phase, 4.8 A, 1.1 kW, IP54/NEMA12, Brake chopper, DC link choke
Variable frequency drive, Part group reference (e.g. DIL): DG1, Rated operational voltage: $U_e = 230 \text{ V AC}$, 3-phase, 240 V AC, 3-phase, Output voltage with V_e : $U_2 = 230 \text{ V AC}$, 3-phase, 240 V AC, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 208 (-15\%) - 240 (+10\%) \text{ V}$, Rated operational current At 150% overload: $I_e = 4.8 \text{ A}$, Note: Rated operational current for a switching frequency of 1 - 12 kHz and an ambient temperature of +50 °C for a 150% overload and +40 °C for a 110% overload, Rated operational current At 110% overload: $I_e = 6.6 \text{ A}$, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm-1 at 50 Hz or 1800 min-1 at 60 Hz, Overload cycle for 60 s every 600 s, at 230 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 1.1 \text{ kW}$, 110 % Overload: $P = 1.5 \text{ kW}$, 150 % Overload: $I_M = 4.6 \text{ A}$, 110 % Overload: $I_M = 6.3 \text{ A}$, Assigned motor rating Note: at 230 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 1 \text{ HP}$, 110 % Overload: $P = 1.5 \text{ HP}$, Assigned motor rating 150 % Overload: $I_M = 4.2 \text{ A}$, 110 % Overload: $I_M = 6 \text{ A}$, Degree of Protecti...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Power XL Frequency Converters

Additional Product Information

General specifications

Product Name Eaton DG1 variable frequency drive Catalog Number 9701-1103-00P Model Code DG1-324D8FB-C54C

EAN 4015081734153 Product Length/Depth 200.9 mm Product Height 327 mm Product Width 153 mm Product Weight 6.1 kg Certifications UL508

CUL

C-Tick

UL File No.: E134360

UkrSEPRO

IEC/EN61800-3

IEC/EN61800-5

Specification for general requirements: IEC/EN 61800-2

UL

RoHS, ISO 9001

UL Category Control No.: NMMS, NMMS7

CE

UL report applies to both US and Canada

Safety requirements: IEC/EN 61800-5

IEC/EN 61800-3

Certified by UL for use in Canada

CSA-C22.2 No. 274-13

EAC Catalog Notes The brake resistors are assigned based on the maximum rated power of the variable frequency drive.

Additional brake resistors and designs (e.g. different duty cycles) are available upon request. Features & Functions

Features Tool-less swapping of fan

Temperature-controlled fan

Parameterization: Fieldbus

Parameterization: Keypad

Parameterization: Power Xpert inControl Functions 4-quadrant operation possible General

Air volume capacity 24 m³/h Cable length C2 ≤ 10 m, Radio interference level, maximum motor cable length

100 m, screened, maximum permissible, Motor feeder

C3 ≤ 50 m, Radio interference level, maximum motor cable length Degree of protection NEMA 12

IP54 Electromagnetic compatibility 1st and 2nd environments (according to EN 61800-3) Environmental class 3C2, 3S2 (Air quality) Fitted with: Internal DC link

PC connection

Breaking resistance

Brake chopper

DC link choke

Add...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DG1-324D8FB-C54C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.