

INDUSTRIAL COMPONENT DATA

**DG1-34061FN-C21C 9702-4004-00P Y7-9702-4004-00P EATON
ELECTRIC DG1-34061FN-C21C Variable frequency drive, 3-..**

Brand: EATON - MOELLER | Manufacturer Part Number: DG1-34061FN-C21C



Manufacturer	EATON - MOELLER
MPN / Reference	DG1-34061FN-C21C
Catalog number	Y7-9702-4004-00P
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-5344284258
Generated	2026-08-05

Product Overview

DG1-34061FN-C21C Variable frequency drive, 3-phase 480 V, 61A, EMC filter, degree of protection IP21

DG1-34061FN-C21C

Eaton DG1 Variable frequency drive, 400 V AC, 3-phase, 61 A, 30 kW, IP21/NEMA1, DC link choke

Variable frequency drive, Part group reference (e.g. DIL): DG1, Rated operational voltage: $U_e = 400 \text{ V AC}$, 3-phase, 480 V AC, 3-phase, 500 V AC, 3-phase, Output voltage with V_e : $U_2 = 400 \text{ V AC}$, 3-phase, 480 V AC, 3-phase, 500 V AC, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 380 (-15\%) - 500 (+10\%) \text{ V}$, Rated operational current At 150% overload: $I_e = 61 \text{ A}$, Note: Rated operational current for a switching frequency of 1 - 10 kHz and an ambient temperature of +50 °C for a 150% overload and +40 °C for a 110% overload, Rated operational current At 110% overload: $I_e = 72 \text{ A}$, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm-1 at 50 Hz or 1800 min-1 at 60 Hz, Overload cycle for 60 s every 600 s, at 400 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 30 \text{ kW}$, 110 % Overload: $P = 37 \text{ kW}$, 150 % Overload: $I_M = 55.2 \text{ A}$, 110 % Overload: $I_M = 68 \text{ A}$, Assigned motor rating Note: at 500 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 37 \text{ kW}$, 110 % Overload: $P = 45 \text{ kW}$, 150 % Overload: $I_M = 54 \text{ A}$, 110 % Overload: $I_M = 65 \text{ A}$, Assigned motor rating Note: at 480 V, 60 Hz, Assi...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Power XL Frequency Converters

Additional Product Information

General specifications

Product Name Eaton DG1 variable frequency drive Catalog Number 9702-4004-00P Model Code DG1-34061FN-C21C

EAN 4015081721474 Product Length/Depth 294 mm Product Height 630 mm Product Width 237.7 mm Product Weight 35.2 kg Certifications C-Tick
IEC/EN 61800-3
UL Category Control No.: NMMS, NMMS7
UL File No.: E134360
CSA-C22.2 No. 274-13
UL report applies to both US and Canada
Certified by UL for use in Canada
IEC/EN61800-3
IEC/EN61800-5
RoHS, ISO 9001
EAC
Specification for general requirements: IEC/EN 61800-2
CUL
CE
Safety requirements: IEC/EN 61800-5
UL508
UkrSEPRO
UL Features & Functions
Features Externally accessible fan
Temperature-controlled fan
Parameterization: Fieldbus
Parameterization: Keypad
Parameterization: Power Xpert inControl General
Air volume capacity 260 m³/h Cable length 200 m, screened, maximum permissible, Motor feeder
C2 <= 10 m, Radio interference level, maximum motor cable length
C3 <= 50 m, Radio interference level, maximum motor cable length Degree of protection IP21
NEMA 1 Electromagnetic compatibility 1st and 2nd environments (according to EN 61800-3) Environmental class 3C2, 3S2
(Air quality) Fitted with: Radio interference suppression filter
IGBT inverter
Additional PCB protection
PC connection
Control unit
Internal DC link
DC link choke
Multi-line graphic display Frame size FS4 Mounting position Vertical Number of slots 2 (expansion) Overvoltage category III
Pollution degree 2 Product Category Variable frequency drives Protecti...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DG1-34061FN-C21C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.