

INDUSTRIAL COMPONENT DATA

DG1-34087FB-C54C 9702-4109-00P Y7-9702-4109-00P EATON ELECTRIC DG1-34087FB-C54C Variable frequency drive, 3-..

Brand: EATON - MOELLER | Manufacturer Part Number: DG1-34087FB-C54C



Manufacturer	EATON - MOELLER
MPN / Reference	DG1-34087FB-C54C
Catalog number	Y7-9702-4109-00P
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-1CCA7D3D15
Generated	2026-08-03

Product Overview

DG1-34087FB-C54C Variable frequency drive, 3-phase 480 V, 87A, EMC filter, Internal braking transistor, protection type IP54

DG1-34087FB-C54C

Eaton DG1 Variable frequency drive, 400 V AC, 3-phase, 87 A, 45 kW, IP54/NEMA12, Brake chopper, DC link choke
Variable frequency drive, Part group reference (e.g. DIL): DG1, Rated operational voltage: $U_e = 400 \text{ V AC}$, 3-phase, 480 V AC, 3-phase, 500 V AC, 3-phase, Output voltage with V_e : $U_2 = 400 \text{ V AC}$, 3-phase, 480 V AC, 3-phase, 500 V AC, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 380 (-15\%) - 500 (+10\%) \text{ V}$, Rated operational current At 150% overload: $I_e = 87 \text{ A}$, Note: Rated operational current for a switching frequency of 1 - 10 kHz and an ambient temperature of +50 °C for a 150% overload and +40 °C for a 110% overload, Rated operational current At 110% overload: $I_e = 105 \text{ A}$, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm-1 at 50 Hz or 1800 min-1 at 60 Hz, Overload cycle for 60 s every 600 s, at 400 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 45 \text{ kW}$, 110 % Overload: $P = 55 \text{ kW}$, 150 % Overload: $I_M = 82.1 \text{ A}$, 110 % Overload: $I_M = 99 \text{ A}$, Assigned motor rating Note: at 500 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 55 \text{ kW}$, 110 % Overload: $P = 55 \text{ kW}$, 150 % Overload: $I_M = 79 \text{ A}$, 110 % Overload: $I_M = 79 \text{ A}$, Assigned...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Power XL Frequency Converters**

Additional Product Information

General specifications

Product Name Eaton DG1 variable frequency drive Catalog Number 9702-4109-00P Model Code DG1-34087FB-C54C

EAN 4015081710973 Product Length/Depth 294 mm Product Height 630 mm Product Width 237.7 mm Product Weight 35.8 kg Certifications IEC/EN 61800-3
Certified by UL for use in Canada
UkrSEPRO
UL508
CE
RoHS, ISO 9001
UL File No.: E134360
UL report applies to both US and Canada
CUL
IEC/EN61800-3
Safety requirements: IEC/EN 61800-5
C-Tick
EAC
UL
UL Category Control No.: NMMS, NMMS7
Specification for general requirements: IEC/EN 61800-2
CSA-C22.2 No. 274-13
IEC/EN61800-5 Catalog Notes The brake resistors are assigned based on the maximum rated power of the variable frequency drive. Additional brake resistors and designs (e.g. different duty cycles) are available upon request. Features & Functions
Features Externally accessible fan
Temperature-controlled fan
Parameterization: Fieldbus
Parameterization: Keypad
Parameterization: Power Xpert inControl Functions 4-quadrant operation possible General
Air volume capacity 260 m³/h Cable length C2 ≤ 10 m, Radio interference level, maximum motor cable length C3 ≤ 50 m, Radio interference level, maximum motor cable length 200 m, screened, maximum permissible, Motor feeder Degree of protection IP54
NEMA 12 Electromagnetic compatibility 1st and 2nd environments (according to EN 61800-3) Environmental class 3C2, 3S2 (Air quality) Fitted with: Brake chopper
DC link choke
Additional PCB protection
Multi-line graphic display...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DG1-34087FB-C54C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.