

## INDUSTRIAL COMPONENT DATA

# DG1-35022FB-C54C 9703-3102-00P EATON ELECTRIC

## Variable frequency drive, 500 V AC, 3-phase, 22 A, 11 kW, IP54..

Brand: EATON - MOELLER | Manufacturer Part Number: DG1-35022FB-C54C



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | EATON - MOELLER                    |
| MPN / Reference | DG1-35022FB-C54C                   |
| Catalog number  | 9703310200P                        |
| Category        | Frequency converter less than 1 kV |
| Minimum order   | 1 Pcs                              |
| Document ID     | EO-243C177644                      |
| Generated       | 2026-08-06                         |

### Product Overview

Variable frequency drive, 500 V AC, 3-phase, 22 A, 11 kW, IP54/NEMA12, Brake chopper, DC link choke  
DG1-35022FB-C54C

Variable frequency drive, Part group reference (e.g. DIL): DG1, Rated operational voltage:  $U_e = 600$  V AC, 3-phase, Output voltage with  $V_e$ :  $U_2 = 600$  V AC, 3-phase, Mains voltage (50/60Hz):  $U_{LN} = 500$  (-10%) -  $600$  (+10%) V, Rated operational current At 150% overload:  $I_e = 22$  A, Note: Rated operational current for a switching frequency of 1 - 6 kHz and an ambient temperature of +50 °C for a 150% overload and +40 °C for a 110% overload, Rated operational current At 110% overload:  $I_e = 27$  A, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: for normal internally and externally ventilated 4 pole , three-phase asynchronous motors with 1500 rpm-1 at 50 Hz or 1800 min-1 at 60 Hz, Overload cycle for 60 s every 600 s, at 525 V, 50 Hz, Assigned motor rating 150 % Overload:  $P = 11$  kW, 110 % Overload:  $P = 15$  kW, 150 % Overload:  $I_M = 17.4$  A, 110 % Overload:  $I_M = 23.4$  A, Assigned motor rating Note: at 600 V, 50 Hz, Assigned motor rating 150 % Overload:  $P = 15$  kW, 110 % Overload:  $P = 18.5$  kW, 150 % Overload:  $I_M = 20.4$  A, 110 % Overload:  $I_M = 25$  A, Assigned motor rating Note: at 600 V, 60 Hz, Assigned motor rating 150 % Overload:  $P = 20$  HP, 110 % Overload:  $P = 25$  HP, Assigned motor rating 150 % Overload:  $I_M = 17$  A, 110 % Overload:  $I_M = 22$  A , Degree of Protect...

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

|              |                                                 |
|--------------|-------------------------------------------------|
| Catalog path | EATON - MOELLER > Power XL Frequency Converters |
|--------------|-------------------------------------------------|

### Additional Product Information

Variable frequency drive, 500 V AC, 3-phase, 22 A, 11 kW, IP54/NEMA12, Brake chopper, DC link chokeVariable frequency

drive, Part group reference (e.g. DIL): DG1, Rated operational voltage:  $U_e = 600 \text{ V AC}$ , 3-phase, Output voltage with  $V_e$ :  $U_2 = 600 \text{ V AC}$ , 3-phase, Mains voltage (50/60Hz):  $U_{LN} = 500 (-10\%) - 600 (+10\%) \text{ V}$ , Rated operational current At 150% overload:  $I_e = 22 \text{ A}$ , Note: Rated operational current for a switching frequency of 1 - 6 kHz and an ambient temperature of +50 °C for a 150% overload and +40 °C for a 110% overload, Rated operational current At 110% overload:  $I_e = 27 \text{ A}$ , Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: for normal internally and externally ventilated 4 pole, three-phase asynchronous motors with 1500 rpm-1 at 50 Hz or 1800 min-1 at 60 Hz, Overload cycle for 60 s every 600 s, at 525 V, 50 Hz, Assigned motor rating 150 % Overload:  $P = 11 \text{ kW}$ , 110 % Overload:  $P = 15 \text{ kW}$ , 150 % Overload:  $I_M = 17.4 \text{ A}$ , 110 % Overload:  $I_M = 23.4 \text{ A}$ , Assigned motor rating Note: at 600 V, 50 Hz, Assigned motor rating 150 % Overload:  $P = 15 \text{ kW}$ , 110 % Overload:  $P = 18.5 \text{ kW}$ , 150 % Overload:  $I_M = 20.4 \text{ A}$ , 110 % Overload:  $I_M = 25 \text{ A}$ , Assigned motor rating Note: at 600 V, 60 Hz, Assigned motor rating 150 % Overload:  $P = 20 \text{ HP}$ , 110 % Overload:  $P = 25 \text{ HP}$ , Assigned motor rating 150 % Overload:  $I_M = 17 \text{ A}$ , 110 % Overload:  $I_M = 22 \text{ A}$ , Degree of Protection: IP54/NEMA12, Interface/field bus (built-in): Modbus RTU, Modbus TCP, BACnet MS/TP, Ethernet IP, Fieldbus connection...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DG1-35022FB-C54C with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.