

INDUSTRIAL COMPONENT DATA

DG1-35208FN-C21C 9703-6006-00P EATON ELECTRIC

Variable frequency drive, 500 V AC, 3-phase, 208 A, 132 kW, IP..

Brand: EATON - MOELLER | Manufacturer Part Number: DG1-35208FN-C21C



Manufacturer	EATON - MOELLER
MPN / Reference	DG1-35208FN-C21C
Catalog number	9703600600P
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-518F1F7F39
Generated	2026-08-05

Product Overview

Variable frequency drive, 500 V AC, 3-phase, 208 A, 132 kW, IP21/NEMA1, DC link choke

DG1-35208FN-C21C

Variable frequency drive, Part group reference (e.g. DIL): DG1, Rated operational voltage: $U_e = 600$ V AC, 3-phase, Output voltage with V_e : $U_2 = 600$ V AC, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 500$ (-10%) - 600 (+10%) V, Rated operational current At 150% overload: $I_e = 208$ A, Note: Rated operational current for a switching frequency of 1 - 6 kHz and an ambient temperature of +50 °C for a 150% overload and +40 °C for a 110% overload, Rated operational current At 110% overload: $I_e = 250$ A, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: for normal internally and externally ventilated 4 pole , three-phase asynchronous motors with 1500 rpm-1 at 50 Hz or 1800 min-1 at 60 Hz, Overload cycle for 60 s every 600 s, at 525 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 132$ kW, 110 % Overload: $P = 160$ kW, 150 % Overload: $I_M = 184$ A, 110 % Overload: $I_M = 224$ A, Assigned motor rating Note: at 600 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 160$ kW, 110 % Overload: $P = 200$ kW, 150 % Overload: $I_M = 197$ A, 110 % Overload: $I_M = 246$ A, Assigned motor rating Note: at 600 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 200$ HP, 110 % Overload: $P = 250$ HP, Assigned motor rating 150 % Overload: $I_M = 192$ A, 110 % Overload: $I_M = 242$ A , Degree of Protection: IP2...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Power XL Frequency Converters**

Additional Product Information

General specifications

Product Name Eaton DG1 variable frequency drive Catalog Number 9703-6006-00P Model Code DG1-35208FN-C21C
EAN 4015081805938 Product Length/Depth 371 mm Product Height 1035 mm Product Width 486 mm Product Weight
116.6 kg Certifications UkrSEPRO
CSA-C22.2 No. 274-13
IEC/EN 61800-3
Safety requirements: IEC/EN 61800-5
CE
Specification for general requirements: IEC/EN 61800-2
UL report applies to both US and Canada
UL508
UL File No.: E134360
EAC
RoHS, ISO 9001
CUL
UL
C-Tick
Certified by UL for use in Canada
IEC/EN61800-3
IEC/EN61800-5
UL Category Control No.: NMMS, NMMS7 Features & Functions
Features Externally accessible fan
Parameterization: Fieldbus
Parameterization: Keypad
Parameterization: Power Xpert inControl General
Air volume capacity 679 m³/h Cable length 200 m, screened, maximum permissible, Motor feeder
C3 ≤ 10 m, Radio interference level, maximum motor cable length Degree of protection NEMA 1
IP21 Electromagnetic compatibility 1st and 2nd environments (according to EN 61800-3) Environmental class 3C2, 3S2 (Air
quality) Fitted with: Control unit
DC link choke
Additional PCB protection
Internal DC link
Multi-line graphic display
PC connection
Radio interference suppression filter
IGBT inverter Frame size FS6 Mounting position Vertical Number of slots 2 (expansion) Overvoltage category III Pollution
degree 2 Product Category Variable frequency drives Protection Finger and back-of-hand proof, Protection against direct
contact (BGV A3, VBG4) Radio in...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DG1-35208FN-C21C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.