

INDUSTRIAL COMPONENT DATA

KT-M25 207603 Y7-207603 EATON ELECTRIC Diaphragm grommet, M25

Brand: EATON - MOELLER | Manufacturer Part Number: KT-M25



Manufacturer	EATON - MOELLER
MPN / Reference	KT-M25
Catalog number	Y7-207603
Category	Cable entry sleeve
Minimum order	1 Pcs
Document ID	EO-DEE9E06DA7
Generated	2026-08-02

Product Overview

Diaphragm grommet, M25

KT-M25

Eaton xEffect Accessories LV systems Accessories and replacement parts for LV switchgear. Diaphragm grommet, M25 Metric cable grommets/diaphragm grommets, degree of protection to IP66, with integral push-through diaphragm, cable entry=M25, drilling dimensions=25.5mm, outer cable diameter=1-18mm, utilization cable NYM/NYY, 4-wire=H03VV-F3x0.75, NYM 4x10mm², PE and thermoplastic elastomer, halogen free, RAL 7035

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Enclosures**

Additional Product Information

General specifications

Product Name Eaton xEffect Accessories cable grommet metric Catalog Number 207603 Model Code KT-M25 EAN 4015082076030 Product Length/Depth 15 mm Product Height 25 mm Product Width 25 mm Product Weight 0.003 kg Complies RoHS conform Product specifications

Special features With integral push-through diaphragm Type General switchboard accessory Features Gastight Watertight

Halogen free Thread size M25 Stress fracture risk Relative high Bore diameter 25.5 mm For outer cable diameter - max 18 mm For outer cable diameter - min 1 mm For wall thickness - max 9.5 mm For wall thickness - min 1 mm Number of cables - max 1 Number of cables - min 1 Opening diameter 25.5 mm Operating temperature - max 40 °C Operating temperature - min -5 °C Suitable for cable diameter - max 18 mm Suitable for cable diameter - min 1 mm Thread size (PG) 0 Pollution

degree 3 Cable entry type M25

Round Surface finishing RAL 7035, light gray Used with Diaphragm grommets

H03VV-F 0.75 mm² (3x)

NYM 10 mm² (4x) Color Light gray (RAL 7035)

Gray Degree of protection IP66 Surface protection Other Accessory/spare part type Cable grommets

Metric diaphragm grommets

Cable management Chemical resistance Resistant against: alcohol, animal and plant fat, brine, light acids, water Material quality Polyethylene (PE) Material Other

Halogen free

PE and thermoplastic elastomer

Silicone free Model Closed Overvoltage category III Temperature resistance Temperature resistant: -40 °C - 80 °C, short-time up....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / KT-M25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.