

INDUSTRIAL COMPONENT DATA

KT-M32 207604 Y7-207604 EATON ELECTRIC Diaphragm grommet, M32

Brand: EATON - MOELLER | Manufacturer Part Number: KT-M32



Manufacturer	EATON - MOELLER
MPN / Reference	KT-M32
Catalog number	Y7-207604
Category	Cable entry sleeve
Minimum order	1 Pcs
Document ID	EO-3C3F79269D
Generated	2026-08-04

Product Overview

Diaphragm grommet, M32

KT-M32

Eaton xEffect Accessories LV systems Accessories and replacement parts for LV switchgear. Diaphragm grommet, M32 Metric cable grommets/diaphragm grommets, degree of protection to IP66, with integral push-through diaphragm, cable entry=M32, drilling dimensions=32.5mm, outer cable diameter=1-25mm use cable NYM/NYY, 4-wire=H03VV-F3x0.75, NYM 4x16/5x10mm², PE and thermoplastic elastomer, halogen free, RAL 7035

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Enclosures

Additional Product Information

General specifications

Product Name Eaton xEffect Accessories LV systems Accessories and replacement parts for LV switchgear Catalog Number 207604 Model Code KT-M32 EAN 4015082076047 Product Length/Depth 20 mm Product Height 35 mm Product Width 35 mm Product Weight 0.004 kg Compliances RoHS conform Product specifications

Special features With integral push-through diaphragm Type General switchboard accessory Features Gastight Halogen free

Watertight Thread size M32 Stress fracture risk Relative high Bore diameter 32.5 mm For outer cable diameter - max 25 mm For outer cable diameter - min 1 mm For wall thickness - max 9.5 mm For wall thickness - min 1 mm Number of cables - max 1 Number of cables - min 1 Opening diameter 32.5 mm Operating temperature - max 40 °C Operating temperature - min -5 °C Suitable for cable diameter - max 25 mm Suitable for cable diameter - min 1 mm Thread size (PG) 0 Pollution

degree 3 Cable entry type Round

M32 Surface finishing RAL 7035, light gray Used with H03VV-F 0.75 mm² (3x)

NYM 16 mm² (4x) or 10 mm² (5x)

Diaphragm grommets Color Light gray (RAL 7035)

Gray Degree of protection IP66 Surface protection Other Accessory/spare part type Metric diaphragm grommets

Cable grommets

Cable management Chemical resistance Resistant against: alcohol, animal and plant fat, brine, light acids, water Material quality Polyethylene (PE) Material Other

Halogen free

PE and thermoplastic elastomer

Silicone free Model Closed Overvoltage category III Temperature resista...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / KT-M32 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.