

INDUSTRIAL COMPONENT DATA

XIOC-8DI 257891 0004519660 EATON ELECTRIC Digital input card for XC100/200, 24 V DC, 8DI

Brand: EATON - MOELLER | Manufacturer Part Number: XIOC-8DI



Manufacturer	EATON - MOELLER
MPN / Reference	XIOC-8DI
Catalog number	0004519660
Category	PLC digital I/O-module
Minimum order	1 Pcs
Document ID	EO-C9BB2BC036
Generated	2026-08-05

Product Overview

Digital input card for XC100/200, 24 V DC, 8DI
XIOC-8DI

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > XC Modular PLC
--------------	----------------------------------

Additional Product Information

Digital input card for XC100/200, 24 V DC, 8DI
Modular programmable controllers XC100 and XC200 offer an outstanding level of scalability. Different CPU performance classes and a wide range of expansion modules (XIOC-Module) are available. The compact modular PLCs XC152 facilitate cost-effective solutions of automation tasks using their computing power, the SmartWire-DT interface as well as a whole range of further interfaces. A particular feature is the ability to integrate the product into modern communication concepts. Data exchange via the Ethernet interface to OPC clients or the integrated WEB servers enables the creation of innovative solutions.

General specifications
Product name Eaton XIOC Accessory Input card
Part no. XIOC-8DI
EAN 4015082578916
Product Length/Depth 100 millimetre
Product height 95 millimetre
Product width 30 millimetre
Product weight 0.135

kilogram
Compliance CE Marked

RoHS Compliant
Certifications UL Listed

CSA Class No.: 2252-01

CSA

CE

EN 50178

UL508

CSA File No.: 012528

UL File No.: E135462

IEC/EN 61131-2

UL Category Control No.: NRAQ

CSA-C22.2 No. 0-M

CSA-C22.2 No. 142-M

ULProduct TradenameXIOCPProduct TypeAccessoryProduct Sub TypeInput cardFeatures & FunctionsElectric connection typeScrew-/spring clamp connectionGeneral informationAdmissible range20.4 - 28.8 V (11.8 - 14.4 V), Power supplyCurrent consumption26 mA, with fitted modulesDegree of protectionIP20Number of channels8Overvoltage categoryII Pollution degree2ProtectionProtection class: 1Repetition rate1 sRes...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XIOC-8DI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.