

INDUSTRIAL COMPONENT DATA

XN-2DI-120/230VAC 140058 Y7-140058 EATON ELECTRIC

Digital input card XI/ON, 120/230VAC, 2DI

Brand: EATON - MOELLER | Manufacturer Part Number: XN-2DI-120/230VAC



Manufacturer	EATON - MOELLER
MPN / Reference	XN-2DI-120/230VAC
Catalog number	Y7-140058
Category	Fieldbus, decentr. periphery - digital I/O module
Minimum order	1 Pcs
Document ID	EO-0D65AF1ED8
Generated	2026-08-05

Product Overview

Digital input card XI/ON, 120/230VAC, 2DI

XN-2DI-120/230VAC

The XI/ON standard I/O system offers the right I/O solution for every application due to its great modularity and large variety of functions. Pluggable modules, hot-swapping of modules, wiring on the basic module screw or tension spring, modules' mechanical coding. The standard gateways support the CANopen bus systems, PROFIBUS-DP deviceNet and Ethernet.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Remote I / O Modules XION

Additional Product Information

General specifications

Product Name Eaton XN Accessory Input card Catalog Number 140058 Model Code XN-2DI-120/230VAC EAN

7640130120167 Product Length/Depth 55.4 mm Product Height 74.1 mm Product Width 12.6 mm Product Weight 0.028 kg

Certifications UL File No.: E205091

CE

IEC/EN 61000-6-4

IEC/EN 6113-2

Certified by UL for use in Canada

CSA-C22.2 No. 142

CSA Class No.: 2252-01, 2252-81

UL 508

CULus

UL report applies to both US and Canada

IEC/EN 61000-6-2

IEC/EN 61131-2

UL Category Control No.: NRAQ, NRAQ7

UL Recognized Features & Functions

Electric connection type Screw-/spring clamp connection Features Fieldbus connection over separate bus coupler possible

General

Current consumption 20 mA, from supply terminal

28 mA, from module bus, Analog input modules Degree of protection IP20 Mounting method Rail mounting possible

Number of channels 2 Product category XN Slice module Suitable for Base modules without C-Connection: 2-/3-wire

Base modules with C-connection: 4-wire Type I/O module Used with XN-S4S-SBBC

XN-S4T-SBBC

XN-S3S-SBB

XN-S3T-SBB Voltage type AC Ambient conditions, mechanical

Drop and topple According to IEC 60068-2-31, free fall according to IEC 60068-2-32 Shock resistance Continuous according to IEC/EN 60068-2-29

Mechanical, According to IEC/EN 60068-2-27 Vibration resistance According to IEC/EN 60068-2-6 Climatic environmental conditions

Ambient operating temperature - min 0 °C Ambient operating temperature - max 55 °C Ambient storage temperature - min -25 °C Ambie...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XN-2DI-120/230VAC with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.