

INDUSTRIAL COMPONENT DATA

XN-32DO-24VDC-0.5A-P 140161 0004560838 EATON

ELECTRIC Digital output block module XI/ON, 24 V DC, 32DO, 0.5A..

Brand: EATON - MOELLER | Manufacturer Part Number: XN-32DO-24VDC-0.5A-P



Manufacturer	EATON - MOELLER
MPN / Reference	XN-32DO-24VDC-0.5A-P
Catalog number	0004560838
Category	Fieldbus, decentr. periphery - digital I/O module
Minimum order	1 Pcs
Document ID	EO-F01F5A82A4
Generated	2026-08-05

Product Overview

Digital output block module XI/ON, 24 V DC, 32DO, 0.5A, pulse-switching
XION Module 32 Digital Outputs 0.5A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Remote I / O Modules XION
--------------	---

Additional Product Information

EL-Nummer (Norway)0004560838Digital output block module XI/ON, 24 V DC, 32DO, 0.5A, pulse-switchingThe XI/ON standard I/O system offers the right I/O solution for every application due to its great modularity and large variety of functions. Pluggable modules, hot-swapping of modules, wiring on the basic module screw or tension spring, modules' mechanical coding. The standard gateways support the CANopen bus systems, PROFIBUS-DP deviceNet and Ethernet.Delivery program

FunctionXI/ON I/O modulesFunctionXN Block moduleShort Description32 Digital output, 24 V DC/0.5 A

Positive switchingFor use withXN-B6T-SBCSBC

XN-B6S-SBCSBCTechnical data

GeneralStandardsEN 61000-6-2

EN 61000-6-4

EN 61131-2Potential isolationYes, through optocouplerAmbient temperatureAmbient temperature, operation0 - +55

°CAmbient temperatureStorage, transport [?]-25 - +85 °CRelative humidityRelative humidity5 - 95 % (indoor), Level RH-2,

no condensation (for storage at 45°C) Ambient conditions, mechanical Degree of Protection IP20 Ambient conditions, mechanical Harmful gases SO₂: 10 (rel. humidity < 75%, no condensation)
H₂S: 1.0 (rel. humidity < 75 %, no condensation) ppm Vibration resistance, operating conditions according to IEC/EN 60068-2-6 Mechanical shock resistance according to IEC 60068-2-27 g Continuous shock resistance (IEC/EN 60068-2-29) According to IEC 60068-2-29 Drop and topple According to IEC 60068-2-31, free fall according to IEC 60068-2-32 Electromagnetic compatibility (EMC) ESD [Air/contact discharge] EN 61000-...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XN-32DO-24VDC-0.5A-P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.