

INDUSTRIAL COMPONENT DATA

XN-2DO-120/230VAC-0.5A 140150 Y7-140150 EATON ELECTRIC Digital output module XI/ON, 120/230VAC, 2DO, 0.5A

Brand: EATON - MOELLER | Manufacturer Part Number: XN-2DO-120/230VAC-0.5A



Manufacturer	EATON - MOELLER
MPN / Reference	XN-2DO-120/230VAC-0.5A
Catalog number	Y7-140150
Category	Fieldbus, decentr. periphery - digital I/O module
Minimum order	1 Pcs
Document ID	EO-3466BF4FA2
Generated	2026-08-04

Product Overview

Digital output module XI/ON, 120/230VAC, 2DO, 0.5A

XN-2DO-120/230VAC-0.5A

The XI/ON standard I/O system offers the right I/O solution for every application due to its great modularity and large variety of functions. Pluggable modules, hot-swapping of modules, wiring on the basic module screw or tension spring, modules' mechanical coding. The standard gateways support the CANopen bus systems, PROFIBUS-DP deviceNet and Ethernet.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Remote I / O Modules XION
--------------	---

Additional Product Information

General specifications

Product Name Eaton XN Output module Catalog Number 140150 Model Code XN-2DO-120/230VAC-0.5A EAN

7640130120198 Product Length/Depth 55.4 mm Product Height 74.1 mm Product Width 12.6 mm Product Weight 0.035 kg

Certifications UL 508

IEC/EN 61000-6-4

Certified by UL for use in Canada

CULus

UL Recognized

CE

IEC/EN 61131-2

IEC/EN 61000-6-2

UL File No.: E205091

UL report applies to both US and Canada

CSA Class No.: 2252-01, 2252-81

CSA-C22.2 No. 142

UL Category Control No.: NRAQ, NRAQ7

IEC/EN 6113-2 Catalog Notes 8 (1 period at 60 Hz) Features & Functions

Electric connection type Screw-/spring clamp connection Features Fieldbus connection over separate bus coupler possible

Fitted with: Connectable sensors for inductive loads

Connectable sensors for lamp loads

Connectable sensors for resistive loads General

Current consumption 35 mA, from module bus, Analog input modules Degree of protection IP20 Mounting method Rail

mounting possible Number of channels 2 Product category XN Slice module Suitable for Base modules with C-connection:

2-wire/3-wire

Base modules with C-connection: 4-wire Type XI/ON I/O module Used with XN-S3T-SBC

XN-S3S-SBC

XN-S4S-SBCS

XN-S4T-SBCS Voltage type AC Ambient conditions, mechanical

Drop and topple According to IEC 60068-2-31, free fall according to IEC 60068-2-32 Shock resistance Mechanical,

According to IEC/EN 60068-2-27

Continuous according to IEC/EN 60068-2-29 Vibration resistance According to IEC/EN 60068-2-6 Climatic environmental...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XN-2DO-120/230VAC-0.5A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.