

INDUSTRIAL COMPONENT DATA

XN-2DO-24VDC-2A-P 140055 Y7-140055 EATON ELECTRIC

Digital output module XI/ON, 24 V DC, 2DO, 2A, pulse-switc..

Brand: EATON - MOELLER | Manufacturer Part Number: XN-2DO-24VDC-2A-P



Manufacturer	EATON - MOELLER
MPN / Reference	XN-2DO-24VDC-2A-P
Catalog number	Y7-140055
Category	Fieldbus, decentr. periphery - digital I/O module
Minimum order	1 Pcs
Document ID	EO-39BB92AA8A
Generated	2026-08-03

Product Overview

Digital output module XI/ON, 24 V DC, 2DO, 2A, pulse-switching

XN-2DO-24VDC-2A-P

The XI/ON standard I/O system offers the right I/O solution for every application due to its great modularity and large variety of functions. Pluggable modules, hot-swapping of modules, wiring on the basic module screw or tension spring, modules' mechanical coding. The standard gateways support the CANopen bus systems, PROFIBUS-DP deviceNet and Ethernet.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Remote I / O Modules XION

Additional Product Information

General specifications

Product Name Eaton XN Output module Catalog Number 140055 Model Code XN-2DO-24VDC-2A-P EAN 7640130120228

Product Length/Depth 55.4 mm Product Height 74.1 mm Product Width 12.6 mm Product Weight 0.028 kg Certifications

IEC/EN 61131-2

CSA-C22.2 No. 142

IEC/EN 61000-6-4

UL Category Control No.: NRAQ, NRAQ7

UL 508

IEC/EN 6113-2

UL File No.: E205091

UL report applies to both US and Canada

CE

UL Recognized

CSA Class No.: 2252-01, 2252-81

Certified by UL for use in Canada

CULus

IEC/EN 61000-6-2 Features & Functions

Electric connection type Screw-/spring clamp connection Features Fieldbus connection over separate bus coupler possible

Fitted with: Connectable sensors for resistive loads

Connectable sensors for lamp loads

Connectable sensors for inductive loads Functions Positive switching

Diagnosis function

Short-circuit protection, outputs available General

Current consumption 50 mA, from supply terminal

33 mA, from module bus, Analog input modules Degree of protection IP20 Mounting method Rail mounting possible

Number of channels 2 Operating frequency < 2 at inductive load Product category XN Slice module Suitable for Base modules with C-connection: 2-wire/3-wire

Base modules with C-connection: 4-wire Switching frequency 10 Hz, with lamp load, Digital outputs 2 Hz

5000 Hz, with resistive load $R_{LO} < 1 \text{ k}\Omega$, Digital outputs Type XI/ON I/O module Used with XN-S4T-SBCS

XN-S3S-SBC

XN-S4S-SBCS

XN-S3T-SBC Voltage type DC Ambient conditions, mechanical

Drop and topple....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XN-2DO-24VDC-2A-P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.