

INDUSTRIAL COMPONENT DATA

XN-2DO-R-CO 140054 Y7-140054 EATON ELECTRIC Digital output module XI/ON, 24 V DC, 2DO(relays), changeover co..

Brand: EATON - MOELLER | Manufacturer Part Number: XN-2DO-R-CO



Manufacturer	EATON - MOELLER
MPN / Reference	XN-2DO-R-CO
Catalog number	Y7-140054
Category	Fieldbus, decentr. periphery - digital I/O module
Minimum order	1 Pcs
Document ID	EO-2A0A681A29
Generated	2026-08-05

Product Overview

Digital output module XI/ON, 24 V DC, 2DO(relays), changeover contact

XN-2DO-R-CO

Eaton XN Digital output module XI/ON, 24 V DC, 2DO(relays), changeover contact XN-2DO-R-CO

The XI/ON standard I/O system offers the right I/O solution for every application due to its great modularity and large variety of functions. Pluggable modules, hot-swapping of modules, wiring on the basic module screw or tension spring, modules' mechanical coding. The standard gateways support the CANopen bus systems, PROFIBUS-DP deviceNet and Ethernet.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Remote I / O Modules XION
--------------	---

Additional Product Information

General specifications

Product Name Eaton XN Output module Catalog Number 140054 Model Code XN-2DO-R-CO EAN 7640130120235

Product Length/Depth 55.4 mm Product Height 74.1 mm Product Width 12.6 mm Product Weight 0.037 kg Certifications IEC/EN 6113-2

IEC/EN 61000-6-2

UL Category Control No.: NRAQ, NRAQ7

UL File No.: E205091

CE

UL Recognized

Certified by UL for use in Canada

CSA-C22.2 No. 142

CSA Class No.: 2252-01, 2252-81

IEC/EN 61000-6-4

CULus

IEC/EN 61131-2

UL 508

UL report applies to both US and Canada Features & Functions

Electric connection type Screw-/spring clamp connection Features Fieldbus connection over separate bus coupler possible

Fitted with: Connectable sensors for lamp loads

Connectable sensors for resistive loads

Connectable sensors for inductive loads General

Current consumption 28 mA, from module bus, Analog input modules

20 mA, from supply terminal Degree of protection IP20 Lifespan, electrical 100,000 Operations (at 5 A)

1,000,000 Operations (at 0.5 A) Mounting method Rail mounting possible Product category XN Slice module Rated load

voltage 230 V AC, 30 V DC Suitable for Base modules without C-Connection: 4-wire Type XI/ON I/O module Used with XN-S4S-SBBS

XN-S4T-SBBS Voltage type AC/DC Ambient conditions, mechanical

Drop and topple According to IEC 60068-2-31, free fall according to IEC 60068-2-32 Shock resistance Continuous according to IEC/EN 60068-2-29

Mechanical, According to IEC/EN 60068-2-27 Vibration resistance According to IEC/EN 60068-2-6 Climat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XN-2DO-R-CO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.