

INDUSTRIAL COMPONENT DATA

XN-2DO-R-NO 140062 Y7-140062 EATON ELECTRIC Digital output module XI/ON, 24 V DC, 2DO(relays), changeover co..

Brand: EATON - MOELLER | Manufacturer Part Number: XN-2DO-R-NO



Manufacturer	EATON - MOELLER
MPN / Reference	XN-2DO-R-NO
Catalog number	Y7-140062
Category	Fieldbus, decentr. periphery - digital I/O module
Minimum order	1 Pcs
Document ID	EO-664FF1F7B5
Generated	2026-08-06

Product Overview

Digital output module XI/ON, 24 V DC, 2DO(relays), changeover contact

XN-2DO-R-NO

Eaton XN Digital output module XI/ON, 24 V DC, 2DO(relays), changeover contact XN-2DO-R-NO

The XI/ON standard I/O system offers the right I/O solution for every application due to its great modularity and large variety of functions. Pluggable modules, hot-swapping of modules, wiring on the basic module screw or tension spring, modules' mechanical coding. The standard gateways support the CANopen bus systems, PROFIBUS-DP deviceNet and Ethernet.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Remote I / O Modules XION
--------------	---

Additional Product Information

General specifications

Product Name Eaton XN Output module Catalog Number 140062 Model Code XN-2DO-R-NO EAN 7640130120259

Product Length/Depth 55.4 mm Product Height 74.1 mm Product Width 12.6 mm Product Weight 0.037 kg Certifications

CSA-C22.2 No. 142

CULus

UL report applies to both US and Canada

IEC/EN 61000-6-4

IEC/EN 6113-2

UL Recognized

Certified by UL for use in Canada

CSA Class No.: 2252-01, 2252-81

IEC/EN 61131-2

UL File No.: E205091

CE

IEC/EN 61000-6-2

UL 508

UL Category Control No.: NRAQ, NRAQ7 Features & Functions

Electric connection type Screw-/spring clamp connection Features Fieldbus connection over separate bus coupler possible

Fitted with: Connectable sensors for inductive loads

Connectable sensors for resistive loads

Connectable sensors for lamp loads General

Current consumption 20 mA, from supply terminal

28 mA, from module bus, Analog input modules Degree of protection IP20 Lifespan, electrical 1,000,000 Operations (at 0.5 A)

100,000 Operations (at 5 A) Mounting method Rail mounting possible Product category XN Slice module Rated load voltage

230 V AC, 30 V DC Suitable for Base modules with C-connection: 4-wire

Base modules without C-Connection: 4-wire Type XI/ON I/O module Used with XN-S4S-SBBS

XN-S4T-SBCS

XN-S4S-SBCS

XN-S4T-SBBS Voltage type AC/DC Ambient conditions, mechanical

Drop and topple According to IEC 60068-2-31, free fall according to IEC 60068-2-32 Shock resistance Continuous according to IEC/EN 60068-2-29

Mechanical, According to IEC/EN 60068...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XN-2DO-R-NO with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.