

INDUSTRIAL COMPONENT DATA

XNE-8DO-24VDC-0.5A-P 140036 Y7-140036 EATON ELECTRIC

Digital output module XI/ON ECO, 24 V DC, 8DO

Brand: EATON - MOELLER | Manufacturer Part Number: XNE-8DO-24VDC-0.5A-P



Manufacturer	EATON - MOELLER
MPN / Reference	XNE-8DO-24VDC-0.5A-P
Catalog number	Y7-140036
Category	Fieldbus, decentr. periphery - digital I/O module
Minimum order	1 Pcs
Document ID	EO-51A347B2E5
Generated	2026-08-05

Product Overview

Digital output module XI/ON ECO, 24 V DC, 8DO

XNE-8DO-24VDC-0.5A-P

Eaton XNE Digital output module XI/ON ECO, 24 V DC, 8DO

The XI/ON standard I/O system adds cost and space-optimized I/O modules and gateways to the XI/ON I/O system. The ECO modules do not need base modules and are fully compatible with the standard XI/ON system. High channel density (up to 16 DI/DO on 13 mm), push-in spring-cage terminals, 8 or 16 channels per module. The ECO gateways support the CANopen bus systems Profibus DP and Ethernet.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Remote I / O Modules XION

Additional Product Information

General specifications

Product Name Eaton XNE Output module Catalog Number 140036 Model Code XNE-8DO-24VDC-0.5A-P EAN

7640130120563 Product Length/Depth 129.5 mm Product Height 74.5 mm Product Width 13 mm Product Weight 0.055 kg

Certifications IEC/EN 61000-6-4

UL report applies to both US and Canada

Rated data for terminations according to IEC/EN 60947-7-1

IEC/EN 61131-2

UL File No.: E205091

CULus

CSA-C22.2 No. 142

UL Category Control No.: NRAQ, NRAQ7

CE

UL Recognized

Certified by UL for use in Canada

CSA Class No.: 2252-01, 2252-81

IEC/EN 6113-2

UL 508

IEC/EN 61000-6-2 Features & Functions

Electric connection type Plug-in connection Features Fieldbus connection over separate bus coupler possible Fitted with:

Connectable sensors for inductive loads

Connectable sensors for resistive loads

Connectable sensors for lamp loads Functions Short-circuit protection, outputs available

Positive switching General

Current consumption 15 mA, from module bus, Analog input modules

3 mA, from supply terminal Degree of protection IP20 Mounting method Rail mounting possible Number of channels 8

Operating frequency As per DC13 to IEC 60947-5-1 at inductive load Product category XNE Slice module Switching

frequency 100 Hz, with resistive load, Digital outputs

10 Hz, with lamp load, Digital outputs Type XI/ON I/O module Voltage type DC Ambient conditions, mechanical

Drop and topple According to IEC 60068-2-31, free fall according to IEC 60068-2-32 Shock resistance Continuous according to IEC/EN 6...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / XNE-8DO-24VDC-0.5A-P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.