

INDUSTRIAL COMPONENT DATA

DILA-XHIT11 101043 Y7-101043 EATON ELECTRIC Auxiliary contact module, raised, 1N/O+1N/C, surface mounting, s..

Brand: EATON - MOELLER | Manufacturer Part Number: DILA-XHIT11



Manufacturer	EATON - MOELLER
MPN / Reference	DILA-XHIT11
Catalog number	Y7-101043
Category	Auxiliary contact block
Minimum order	5 Pcs
Document ID	EO-79DCD9C232
Generated	2026-08-05

Product Overview

Auxiliary contact module, raised, 1N/O+1N/C, surface mounting, screw connection

DILA-XHIT11

Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 2 pole, Ith= 16 A, 1 N/O, 1 NC, Front fixing, Screw terminals, MSC

Auxiliary contact module, with interlocked opposing contacts, Switching elements according to EN 50005, Version E combinations correspond to EN 50011 and are to be preferred., The DC operated contactor DILA(C)-22 must only be combined with 2-pole auxiliary contacts., Function: for combination with electrical wiring links, 2 pole, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, Rated operational current AC-15 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, Mounting type: Front fixing, For use with: DILM7..., DILM9..., DILM12..., DILM15..., DILL..., MSC-D...M7(9, 12, 15)..., MSC-R...M7(9, 12), Type: high version, Instructions: Interlocked opposing contacts according to IEC/EN 60947-5-1 appendix L, in

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILA Accessory Auxiliary contact module Catalog Number 101043 Model Code DILA-XHIT11 EAN 4015081009381 Product Length/Depth 55 mm Product Height 38 mm Product Width 36 mm Product Weight 0.039 kg Certifications CSA
UL

VDE 0660

UL Category Control No.: NKCR

UL 508

UL File No.: E29184

CE

CSA Class No.: 3211-03

CSA File No.: 012528

IEC/EN 60947-4-1

CSA-C22.2 No. 14-05

IEC/EN 60947 Features & Functions

Features Interlocked opposing contacts within an auxiliary contact module (according to IEC 60947-5-1 Annex L) Functions
For combination with electrical wiringlinks Fitted with: Interlocked opposing contacts

Switching elements according to EN 50005 Number of poles Two-pole Electric connection type Screw connection General
Degree of protection IP20 Shock resistance 7 g, N/O auxiliary contact, Basic unit with auxiliary contact module, Mechanical,
according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

5 g, N/C auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27,
Half-sinusoidal shock 10 ms Lifespan, electrical 1,300,000 Operations (at 230 V, AC-15, 3 A) Model Top mounting Mounting
method Front fastening Overvoltage category III Pollution degree 3 Protection Finger and back-of-hand proof, Protection
against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 6000 V
6000 V AC Type Front mounting auxiliary contact, high version Climatic....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILA-XHIT11 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.