

INDUSTRIAL COMPONENT DATA

DILA-XHIT22 101044 Y7-101044 EATON ELECTRIC Auxiliary contact module, raised, 2N/O+2N/C, surface mounting, s..

Brand: EATON - MOELLER | Manufacturer Part Number: DILA-XHIT22



Manufacturer	EATON - MOELLER
MPN / Reference	DILA-XHIT22
Catalog number	Y7-101044
Category	Auxiliary contact block
Minimum order	5 Pcs
Document ID	EO-CA61819C7E
Generated	2026-08-02

Product Overview

Auxiliary contact module, raised, 2N/O+2N/C, surface mounting, screw connection

DILA-XHIT22

Eaton Moeller® series DILA Auxiliary contact module, Type: high version, 4 pole, Ith= 16 A, 2 N/O, 2 NC, Front fixing, Screw terminals, MSC

Auxiliary contact module, Connection technique: Screw terminals, Contacts N/O = Normally open: 2 N/O, Contacts N/C = Normally closed: 2 NC, For use with: DILM7..., DILM9..., DILM12..., DILM15..., DILL..., MSC-D...M7(9, 12, 15)..., MSC-R...M7(9, 12)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILA Accessory Auxiliary contact module Catalog Number 101044 Model Code DILA-XHIT22 EAN 4015081009398 Product Length/Depth 55 mm Product Height 38 mm Product Width 36 mm Product Weight 0.052 kg Certifications CSA Class No.: 3211-03

CSA

CE

CSA File No.: 012528

IEC/EN 60947

UL 508

CSA-C22.2 No. 14-05

IEC/EN 60947-4-1

UL

UL File No.: E29184

UL Category Control No.: NKCR

VDE 0660 Features & Functions

Features Interlocked opposing contacts within an auxiliary contact module (according to IEC 60947-5-1 Annex L) Functions

For combination with electrical wiringlinks Fitted with: Interlocked opposing contacts

Switching elements according to EN 50005 Number of poles Four-pole Electric connection type Screw connection General

Degree of protection IP20 Shock resistance 7 g, N/O auxiliary contact, Basic unit with auxiliary contact module, Mechanical,

according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

5 g, N/C auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27,

Half-sinusoidal shock 10 ms Lifespan, electrical 1,300,000 Operations (at 230 V, AC-15, 3 A) Model Top mounting Mounting

method Front fastening Overvoltage category III Pollution degree 3 Protection Finger and back-of-hand proof, Protection

against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 6000 V AC

6000 V Type Front mounting auxiliary contact, high version Climatic...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILA-XHIT22 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.