

INDUSTRIAL COMPONENT DATA

DILA-XHIV22 276429 Y7-276429 EATON ELECTRIC Auxiliary contact module, raised, 1N/O+1N/O early+1N/C+1N/C late..

Brand: EATON - MOELLER | Manufacturer Part Number: DILA-XHIV22



Manufacturer	EATON - MOELLER
MPN / Reference	DILA-XHIV22
Catalog number	Y7-276429
Category	Auxiliary contact block
Minimum order	5 Pcs
Document ID	EO-6F3C278006
Generated	2026-08-05

Product Overview

Auxiliary contact module, raised, 1N/O+1N/O early+1N/C+1N/C late, surface mounting, screw connection

DILA-XHIV22

Eaton Moeller® series DILA Auxiliary contact module, 4 pole, Ith= 16 A, 1 N/O, 1 N/OE, 1 NC, 1 NCL, Front fixing, Screw terminals, DILA, DILM7 - DILM38

Auxiliary contact module, Function: for standard applications, 4 pole, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, Rated operational current AC-15 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 1 N/O, Contacts N/OE: NO early-make: 1 N/OE, Contacts N/C = Normally closed: 1 NC, Contacts NCL=NC late-break: 1 NCL, Mounting type: Front fixing, For use with: DILA(C)..., DILM(C)7..., DILM(C)9..., DILM(C)12..., DILM(C)15..., DILM(C)17..., DILM(C)25..., DILM(C)32..., DILM38..., DILMP20..., DILMP32..., DILMP45..., DILL..., DILMF8..., DILMF11..., DILMF14..., DILMF17..., DILMF25..., DILMF32..., Type: Front mounting auxiliary contact, Instructions: Auxiliary contacts used as mirror contacts according to IEC/EN 60947-4-1 Appendix F (not N/C late open), Code number and vers

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILA Accessory Auxiliary contact module Catalog Number 276429 Model Code DILA-XHIV22 EAN 4015082764296 Product Length/Depth 45 mm Product Height 38 mm Product Width 36 mm Product Weight 0.048 kg Certifications UL File No.: E29184

UL

UL Category Control No.: NKCR

CSA

IEC/EN 60947-4-1

VDE 0660

CSA-C22.2 No. 14-05

IEC/EN 60947

CE

CSA Class No.: 3211-03

CSA File No.: 012528

UL 508 Features & Functions

Functions For standard applications Number of poles Four-pole Electric connection type Screw connection General Degree of protection IP20 Shock resistance 5 g, N/C auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

7 g, N/O auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27,

Half-sinusoidal shock 10 ms Lifespan, electrical 1,300,000 Operations (at 230 V, AC-15, 3 A) Lifespan, mechanical

10,000,000 Operations (AC operated)

10,000,000 Operations (DC operated) Model Top mounting Mounting method Front fastening Connection Screw terminals

Operating frequency 9000 Operations/h Overvoltage category III Pollution degree 3 Protection Finger and back-of-hand

proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 6000

V AC Type Front mounting auxiliary contact Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILA-XHIV22 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.