

INDUSTRIAL COMPONENT DATA

DILM150-XHICV22 278049 Y7-278049 EATON ELECTRIC

Auxiliary contact module, 1N/O+1N/O early+1N/C+1N/C late, sp..

Brand: EATON - MOELLER | Manufacturer Part Number: DILM150-XHICV22



Manufacturer	EATON - MOELLER
MPN / Reference	DILM150-XHICV22
Catalog number	Y7-278049
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-BF7E5757DC
Generated	2026-08-06

Product Overview

Auxiliary contact module, 1N/O+1N/O early+1N/C+1N/C late, spring clamp connection

DILM150-XHICV22

Eaton Moeller® series DILM Auxiliary contact module, 4 pole, Ith= 16 A, 1 N/O, 1 N/OE, 1 NC, 1 NCL, Front fixing, Spring-loaded terminals, DILMC40 - DILMC150

Auxiliary contact module, Function: for standard applications, 4 pole, Connection technique: Spring-loaded terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 6 A, Rated operational current AC-15 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 1 N/O, Contacts N/OE: NO early-make: 1 N/OE, Contacts N/C = Normally closed: 1 NC, Contacts NCL=NC late-break: 1 NCL, Mounting type: Front fixing, For use with: DILMC40..., DILMC50..., DILMC65..., DILMC80..., DILMC95..., DILMC115..., DILMC150..., Type: Front mounting auxiliary contact , Instructions: Auxiliary contacts used as mirror contacts according to IEC/EN 60947-4-1 Appendix F (not N/C late open)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM auxiliary contact module Catalog Number 278049 Model Code

DILM150-XHICV22 EAN 4015082780494 Product Length/Depth 39 mm Product Height 46 mm Product Width 45 mm

Product Weight 0.055 kg Certifications CSA File No.: 012528

IEC/EN 60947

CSA Class No.: 3211-03

VDE 0660

CSA

CSA-C22.2 No. 14-05

UL File No.: E29184

UL Category Control No.: NKCR

UL

IEC/EN 60947-4-1

UL 508

CE Features & Functions

Functions For standard applications Number of poles Four-pole Electric connection type Spring clamp connection General Lifespan, electrical 1,300,000 Operations (at 230 V, AC-15, 3 A) Model Top mounting Mounting method Front fastening Overvoltage category III Pollution degree 3 Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 6000 V AC Type Front mounting auxiliary contact Ambient conditions, mechanical

Shock resistance 5 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Ambient operating temperature (enclosed) - min -25 °C Ambient operating temperature (enclosed) - max 40 °C Ambient storage temperature - min -40 °C Ambient storage temperature - max 80 °C Climatic proo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM150-XHICV22 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.