

INDUSTRIAL COMPONENT DATA

DILM820-XHI11V-SI 208283 Y7-208283 EATON ELECTRIC

Auxiliary contact module 1 NO early-make + 1 NC late-break..

Brand: EATON - MOELLER | Manufacturer Part Number: DILM820-XHI11V-SI



Manufacturer	EATON - MOELLER
MPN / Reference	DILM820-XHI11V-SI
Catalog number	Y7-208283
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-0C2231D974
Generated	2026-08-04

Product Overview

Auxiliary contact module;1 NO early-make + 1 NC late-break;laterally inside;screw connection

DILM820-XHI11V-SI

Eaton Moeller® series DILM Auxiliary contact module, 2 pole, Ith= 10 A, 1 N/OE, 1 NCL, Side mounted, Screw terminals, DILM250 - DILH2600

Auxiliary contact module, Function: for standard applications, 2 pole, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, Rated operational current AC-15 380 V 400 V 415 V: Ie= 4 A, Rated operational current AC-15 380 V 400 V 500 V: Ie= 4 A, Contacts N/OE: 1 N/OE, Contacts NCL=NC late-break: 1 NCL, Mounting type: Side mounted, For use with: DILM250 - DILH2600, DILDC300 - DILDC600, Type: Side-mounting auxiliary contacts

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors more than 170 A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM auxiliary contact module Catalog Number 208283 Model Code

DILM820-XHI11V-SI EAN 4015082082833 Product Length/Depth 77 mm Product Height 77 mm Product Width 15 mm

Product Weight 0.04 kg Certifications CSA Class No.: 3211-04

UL

VDE 0660

UL Category Control No.: NKCR

CE

UL 508

IEC/EN 60947-4-1

CSA

CSA File No.: 012528

CSA-C22.2 No. 14-05

UL File No.: E29184

IEC/EN 60947 Catalog Notes Rated operational current: Switch-on and switch-off conditions based on DC-13, time constant as specified. Features & Functions

Functions For standard applications Number of poles Two-pole Electric connection type Screw connection General Lifespan, electrical 1,300,000 Operations (at 230 V, AC-15, 3 A) Model Top mounting Mounting method Side mounting Overvoltage category III Pollution degree 3 Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 6000 V AC

6000 V Type Side-mounting auxiliary contacts Climatic environmental conditions

Ambient operating temperature - min -40 °C Ambient operating temperature - max 60 °C Ambient operating temperature (enclosed) - min 25 °C Ambient operating temperature (enclosed) - max 40 °C Ambient storage temperature - min 40 °C

Ambient storage temperature - max 80 °C Climatic proofing Damp heat, cyclic, to IEC 60068-2-30

Damp heat, constant, to IEC 60068-2-78 Terminal capacities

Terminal capacity (flexible wi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM820-XHI11V-SI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.