


INDUSTRIAL COMPONENT DATA

DILA-22(24VDC)-PI 199218 Y7-199218 EATON ELECTRIC

DILA-22(24VDC)-PI

Brand: EATON - MOELLER | Manufacturer Part Number: DILA-22(24VDC)-PI



Manufacturer	EATON - MOELLER
MPN / Reference	DILA-22(24VDC)-PI
Catalog number	Y7-199218
Category	Contactor relay
Minimum order	1 Pcs
Document ID	EO-6505F7CF0B
Generated	2026-08-05

Product Overview

DILA-22(24VDC)-PI

Eaton Moeller® series DILA Contactor relay, 24 V DC, 2 N/O, 2 NC, Push in terminals, DC operation

Contactor relay, Product range: DILA relays, Application: Contactor relays, Description: Basic devices with positive operation contacts, Connection technique: Push in terminals, Rated operational current AC-15 220 V 230 V 240 V: I_e = 4 A, 380 V 400 V 415 V: I_e = 4 A, Contacts N/O = Normally open: 2 N/O, Contacts N/C = Normally closed: 2 NC, Code number and version of combination Distinctive number: 22E, Can be combined with auxiliary contact module: DILA-XHI(V)...-PI, Actuating voltage: 24 V DC, Voltage AC/DC: DC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, built-in suppressor circuit, Integrated varistor suppressor circuit., Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILA Control relay Catalog Number 199218 Model Code DILA-22(24VDC)-PI EAN 4015081973026 Product Length/Depth 75 mm Product Height 68 mm Product Width 45 mm Product Weight 0.287 kg

Certifications EN 60947-5-1

IEC/EN 60947

VDE 0660

CSA File No.: 012528

CSA Class No.: 3211-03

UL File No.: E29184

UL 508

CSA-C22.2 No. 14-05

CE marking

UL Category Control No.: NKCR

UL

CSA Features & Functions

Features Positive operating contacts to EN 60947-5-1 appendix L, including auxiliary contact module Fitted with: Positive operation contacts

Suppressor circuit

Built-in suppressor circuit

Varistor suppressor circuit General

Application Contactor relays Degree of protection IP20 Shock resistance 7 g, N/O auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

5 g, N/C auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27,

Half-sinusoidal shock 10 ms Lifespan, mechanical 20,000,000 Operations (DC operated) Mounting method DIN-rail/screw

Connection Push in terminals Operating frequency 9000 Operations/h Overvoltage category III Pollution degree 3 Product category DILA relays Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front

(EN 50274) Rated impulse withstand voltage (Uimp) 6000 V AC Voltage type DC Climatic environmental conditions

Ambient operating temperature -....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILA-22(24VDC)-PI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.