

INDUSTRIAL COMPONENT DATA

DILA-22(TVC200) 276410 XTRE10B22DH EATON ELECTRIC

Contact relay, 2N/O+2N/C, AC

Brand: EATON - MOELLER | Manufacturer Part Number: DILA-22(TVC200)



Manufacturer	EATON - MOELLER
MPN / Reference	DILA-22(TVC200)
Catalog number	XTRE10B22DH
Category	Contact relay
Minimum order	1 Pcs
Document ID	EO-7D8BFBE620
Generated	2026-08-06

Product Overview

Contact relay, 2N/O+2N/C, AC

Auxiliary Contactor; 3 NO + 1 NC; Connection screw; T V C200

Contact relay, TVC200: 200 V 50 Hz/200-220 V 60 Hz, N/O = Normally open: 2 N/O, N/C = Normally closed: 2 NC, Screw terminals, AC operation

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

Contact relay, TVC200: 200 V 50 Hz/200-220 V 60 Hz, N/O = Normally open: 2 N/O, N/C = Normally closed: 2 NC, Screw terminals, AC operation
Contact relay, Product range: DILA relays, Application: Contactor relays, Description: Basic devices with positive operation contacts, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: I_e = 4 A, 380 V 400 V 415 V: I_e = 4 A, Contacts N/O = Normally open: 2 N/O, Contacts N/C = Normally closed: 2 NC, Code number and version of combination Distinctive number: 22D, Can be combined with auxiliary contact module: DILA-XHI(V)..., Actuating voltage: TVC200: 200 V 50 Hz/200-220 V 60 Hz, Voltage AC/DC: AC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA
Delivery program

Product rangeDILA relaysApplicationContactor relaysDescriptionBasic devices with positive operation contactsConnection techniqueScrew terminalsRated operational currentAC-15220 V 230 V 240 V [I_e]4 AAC-15380 V 400 V 415 V [I_e]4 AContactsN/O = Normally open2 N/OON/C = Normally closed2 NCContact sequenceCode number and version of combinationDistinctive number22DCan be combined with auxiliary contact moduleDILA-XHI(V)...Actuating voltageTVC200:

200 V 50 Hz/200-220 V 60 HzVoltage AC/DCAC operationConnection to SmartWire-DTnoInstructionsContact numbers to
EN 50011

Coil terminal markings to EN 50005Technical data

GeneralStandardsIEC...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILA-22(TVC200) with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.