


INDUSTRIAL COMPONENT DATA

DILA-40(24VDC)-PI 199208 Y7-199208 EATON ELECTRIC Auxiliary Contactor 4 NO Screw connection 24 V DC Push-in

Brand: EATON - MOELLER | Manufacturer Part Number: DILA-40(24VDC)-PI



Manufacturer	EATON - MOELLER
MPN / Reference	DILA-40(24VDC)-PI
Catalog number	Y7-199208
Category	Contactor relay
Minimum order	1 Pcs
Document ID	EO-73E47B138A
Generated	2026-08-04

Product Overview

Auxiliary Contactor; 4 NO; Screw connection; 24 V DC; Push-in

DILA-40(24VDC)-PI

Eaton Moeller® series DILA Contactor relay, 24 V DC, 4 N/O, Push in terminals, DC operation

Contactor relay, Product range: DILA relays, Application: Contactor relays, Description: Basic devices with positive operating contacts, Connection technique: Push terminals, Nominal operating current AC-15 220 V 230 V 240 V: Ie= 4 A, 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 4 N/O, Code number and combination version Distinctive number: 40E, Combinable with auxiliary contact module: DILA-XHI(V)...-PI, Actuation voltage: 24 V DC, AC/DC voltage: DC operation, Degree of protection: IP20, Instructions: Contact numbers according to EN 50011, Coil terminal marks according to EN 50005, Built-in suppressor circuit, Integrated varistor suppressor circuit., Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILA Control relay Catalog Number 199208 Model Code DILA-40(24VDC)-PI EAN 4015081972920 Product Length/Depth 75 mm Product Height 68 mm Product Width 45 mm Product Weight 0.287 kg

Certifications IEC/EN 60947

EN 60947-5-1

VDE 0660

CSA File No.: 012528

CSA Class No.: 3211-03

UL File No.: E29184

UL 508

CSA-C22.2 No. 14-05

CE marking

UL Category Control No.: NKCR

UL

CSA Features & Functions

Features Positive operating contacts to EN 60947-5-1 appendix L, including auxiliary contact module Fitted with: Built-in suppressor circuit

Varistor suppressor circuit

Positive operation contacts

Suppressor circuit General

Application Contactor relays Degree of protection IP20 Shock resistance 5 g, N/C auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

7 g, N/O auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27,

Half-sinusoidal shock 10 ms Lifespan, mechanical 20,000,000 Operations (DC operated) Mounting method DIN-rail/screw

Connection Push in terminals Operating frequency 9000 Operations/h Overvoltage category III Pollution degree 3 Product

category DILA relays Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front

(EN 50274) Rated impulse withstand voltage (Uimp) 6000 V AC Voltage type DC Climatic environmental conditions

Ambient operating temperature -....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILA-40(24VDC)-PI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.