

INDUSTRIAL COMPONENT DATA

DILAS-R44(110V50HZ,120V60HZ) 191732 Y7-191732 EATON ELECTRIC Safety contactor relay, 4N/O+4N/C, electronical..

Brand: EATON - MOELLER | Manufacturer Part Number: DILAS-R44(110V50HZ,120V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILAS-R44(110V50HZ,120V60HZ)
Catalog number	Y7-191732
Category	Contactor relay
Minimum order	1 Pcs
Document ID	EO-97ADD8286B
Generated	2026-08-06

Product Overview

Safety contactor relay, 4N/O+4N/C, electronically-compatible auxiliary contact, AC

DILAS-R44(110V50HZ,120V60HZ)

Eaton Moeller® series DILA Safety contactor relay, 110 V 50 Hz, 120 V 60 Hz, N/O = Normally open: 4 N/O, N/C = Normally closed: 4 NC, Screw terminals, AC operation DILAS-R44(110V50HZ,120V60HZ)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Contactors up to 170A**

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILA Control relay Catalog Number 191732 Model Code

DILAS-R44(110V50HZ,120V60HZ) EAN 4015081922451 Product Length/Depth 117 mm Product Height 69 mm Product

Width 45 mm Product Weight 0.288 kg Certifications CE

CSA Class No.: 3211-03

CSA File No.: 012528

VDE 0660

CSA-C22.2 No. 14-05

CSA

UL 508

EN 60947-5-1

UL

UL File No.: E29184

IEC/EN 60947

IEC/EN 60947-4-1

UL Category Control No.: NKCR Features & Functions

Features Positive operating contacts to EN 60947-5-1 appendix L, including auxiliary contact module Fitted with: Top mounting auxiliary contacts with interlocked opposing contacts General

Application Contactor relays Degree of protection IP20 Shock resistance 7 g, N/O auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

5 g, N/C auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27,

Half-sinusoidal shock 10 ms Lifespan, mechanical 20,000,000 Operations (AC operated) Mounting method DIN-rail/screw

Connection Screw terminals Operating frequency 9000 Operations/h Overvoltage category III Pollution degree 3 Product

category DILAS safety contactor relays Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 6000 V AC Voltage type AC Climatic environmental conditions

Ambient operating temperature -...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILAS-R44(110V50HZ,120V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.