

INDUSTRIAL COMPONENT DATA

DILAS-R44(24VDC) 191720 Y7-191720 EATON ELECTRIC

Electronic control relay, rated operating voltage 24VDC, 8 ..

Brand: EATON - MOELLER | Manufacturer Part Number: DILAS-R44(24VDC)



Manufacturer	EATON - MOELLER
MPN / Reference	DILAS-R44(24VDC)
Catalog number	Y7-191720
Category	Contacteur relay
Minimum order	1 Pcs
Document ID	EO-F926BC72A1
Generated	2026-08-05

Product Overview

Electronic control relay, rated operating voltage 24VDC, 8 digital inputs 24VDC, 2 inputs can be used as analog inputs, 4 relay outputs, keyboard, LCD display, time switch, menu also available in Cyrillic
DILAS-R44(24VDC)

Eaton Moeller® series DILA Safety contactor relay, 24 V DC, N/O = Normally open: 4 N/O, N/C = Normally closed: 4 NC, Screw terminals, DC operation DILAS-R44(24VDC)

Safety contactor relay, Application: Contactor relays, Connection technique: Screw terminals, Description: Basic devices and top mounting auxiliary contacts with interlocked opposing contacts, (except microswitches), 2 electronic-compatible auxiliary microswitch contacts (1 NO + 1 NC), Contacts N/O = Normally open: 4 N/O, Contacts N/C = Normally closed: 4 NC, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, built-in suppressor circuit', Voltage AC/DC: DC operation

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILA Control relay Catalog Number 191720 Model Code DILAS-R44(24VDC) EAN 4015081922338 Product Length/Depth 117 mm Product Height 69 mm Product Width 45 mm Product Weight 0.354 kg

Certifications UL File No.: E29184

CSA Class No.: 3211-03

CSA

UL Category Control No.: NKCR

CSA-C22.2 No. 14-05

EN 60947-5-1

VDE 0660

CE

CSA File No.: 012528

IEC/EN 60947

UL 508

IEC/EN 60947-4-1

UL Features & Functions

Features Positive operating contacts to EN 60947-5-1 appendix L, including auxiliary contact module Fitted with:
Suppressor circuit

Top mounting auxiliary contacts with interlocked opposing contacts

Built-in suppressor circuit General

Application Contactor relays Degree of protection IP20 Shock resistance 5 g, N/C auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

7 g, N/O auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27,

Half-sinusoidal shock 10 ms Lifespan, mechanical 20,000,000 Operations (DC operated) Mounting method DIN-rail/screw

Connection Screw terminals Operating frequency 9000 Operations/h Overvoltage category III Pollution degree 3 Product

category DILAS safety contactor relays Protection Finger and back-of-hand proof, Protection against direct contact when

actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 6000 V AC Voltage type DC Climatic environmental
conditi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILAS-R44(24VDC) with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.