

INDUSTRIAL COMPONENT DATA

DILAT-12(RDC24) 190969 Y7-190969 EATON ELECTRIC

Contacteur Auxilar Narrow 1 NO + 2 NC Connection screw RDC24

Brand: EATON - MOELLER | Manufacturer Part Number: DILAT-12(RDC24)



Manufacturer	EATON - MOELLER
MPN / Reference	DILAT-12(RDC24)
Catalog number	Y7-190969
Category	Contacteur relay
Minimum order	1 Pcs
Document ID	EO-7F44F541A4
Generated	2026-08-06

Product Overview

Contacteur Auxilar Narrow; 1 NO + 2 NC; Connection screw; RDC24

DILAT-12(RDC24)

Eaton Moeller® series DILAT Contactor relay, 24 V DC, 1 N/O, 2 NC, Screw terminals, DC operation

Contacteur relay, Product range: Contacteur relays DILAT, Application: Contacteur relays, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, 380 V 400 V 415 V: Ie= 1.9 A, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 2 NC, Actuating voltage: 24 V DC, Voltage AC/DC: DC operation, Degree of Protection: IP20, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILAT Control relay Catalog Number 190969 Model Code DILAT-12(RDC24) EAN 4015081911929 Product Length/Depth 77.5 mm Product Height 70.1 mm Product Width 27 mm Product Weight 0.175 kg

General

Mounting method DIN-rail/screw Voltage type DC Electrical rating

Rated operational current (Ie) at AC-15, 380 V, 400 V, 415 V 1.9 A Magnet system

Rated control supply voltage (Us) at AC, 50 Hz - min 0 V Rated control supply voltage (Us) at AC, 50 Hz - max 0 V Rated

control supply voltage (Us) at AC, 60 Hz - min 0 V Rated control supply voltage (Us) at AC, 60 Hz - max 0 V Rated control supply voltage (Us) at DC - min 24 V Rated control supply voltage (Us) at DC - max 24 V Contacts

Number of auxiliary contacts (normally closed contacts) 2 Number of auxiliary contacts (normally open contacts) 1

ETIM for 190969 Low-voltage industrial controls and switchgear (EC000196)

Feature Name

Feature Value

Rated control supply voltage AC 50 Hz (EF003978)

0 V

Rated control supply voltage AC 60 Hz (EF003979)

0 V

Rated control supply voltage DC (EF003980)

24 V

Voltage type for actuating (EF008242)

DC

Rated operation current (EF007679)

10 A

Rated operation current Ie, 400 V (EF001378)

1.9 A

Mounting method (EF000003)

DIN-rail/screw

With LED indication (EF005950)

No

Suitable for manual operation (EF002978)

No

Interface (EF000594)

No

Number of auxiliary contacts as normally closed contact (EF001377)

2

Number of auxiliary contacts as normally open conta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILAT-12(RDC24) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.