

INDUSTRIAL COMPONENT DATA

DILAT-30(230V50HZ/240V60HZ) 190990 Y7-190990 EATON ELECTRIC Contactor Auxilar Narrow 3 NO Connection screw 2..

Brand: EATON - MOELLER | Manufacturer Part Number: DILAT-30(230V50HZ/240V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILAT-30(230V50HZ/240V60HZ)
Catalog number	Y7-190990
Category	Contactor relay
Minimum order	1 Pcs
Document ID	EO-3D21D6BDED
Generated	2026-08-06

Product Overview

Contactor Auxilar Narrow; 3 NO; Connection screw; 230 V 50HZ 240 V/60HZ

DILAT-30(230V50HZ/240V60HZ)

Eaton Moeller® series DILAT Contactor relay, 230 V 50 Hz, 240 V 60 Hz, 3 N/O, Screw terminals, AC operation

Contactor relay, Product range: Contactor relays DILAT, Application: Contactor relays, Connection technique: Screw

terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, 380 V 400 V 415 V: Ie= 1.9 A, Contacts N/O =

Normally open: 3 N/O, Actuating voltage: 230 V 50 Hz, 240 V 60 Hz, Voltage AC/DC: AC operation, Degree of Protection:

IP20, Standards: IEC/EN 60947, VDE 0660

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILAT Control relay Catalog Number 190990 Model Code

DILAT-30(230V50HZ/240V60HZ) EAN 4015081912131 Product Length/Depth 77.5 mm Product Height 70.1 mm Product

Width 27 mm Product Weight 0.175 kg General

Mounting method DIN-rail/screw Voltage type AC Electrical rating

Rated operational current (Ie) at AC-15, 380 V, 400 V, 415 V 1.9 A Magnet system

Rated control supply voltage (Us) at AC, 50 Hz - min 230 V Rated control supply voltage (Us) at AC, 50 Hz - max 230 V

Rated control supply voltage (Us) at AC, 60 Hz - min 240 V Rated control supply voltage (Us) at AC, 60 Hz - max 240 V

Rated control supply voltage (Us) at DC - min 0 V Rated control supply voltage (Us) at DC - max 0 V Contacts

Number of auxiliary contacts (normally closed contacts) 0 Number of auxiliary contacts (normally open contacts) 3

ETIM for 190990 Low-voltage industrial controls and switchgear (EC000196)

Feature Name

Feature Value

Rated control supply voltage AC 50 Hz (EF003978)

230 V

Rated control supply voltage AC 60 Hz (EF003979)

240 V

Rated control supply voltage DC (EF003980)

0 V

Voltage type for actuating (EF008242)

AC

Rated operation current (EF007679)

10 A

Rated operation current Ie, 400 V (EF001378)

1.9 A

Mounting method (EF000003)

DIN-rail/screw

With LED indication (EF005950)

No

Suitable for manual operation (EF002978)

No

Interface (EF000594)

No

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts a...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILAT-30(230V50HZ/240V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.