

INDUSTRIAL COMPONENT DATA

**DILDC400/22(RDS250) 186872 Y7-186872 EATON ELECTRIC
DC contactor, 2 pole + 2 N/O + 2 N/C, 400 A/DC-1, 1000V**

Brand: EATON - MOELLER | Manufacturer Part Number: DILDC400/22(RDS250)



Manufacturer	EATON - MOELLER
MPN / Reference	DILDC400/22(RDS250)
Catalog number	Y7-186872
Category	Power contactor, DC switching
Minimum order	1 Pcs
Document ID	EO-0E09D582F6
Generated	2026-08-04

Product Overview

DC contactor, 2 pole + 2 N/O + 2 N/C, 400 A/DC-1, 1000V

DILDC400/22(RDS250)

Eaton Moeller® series DILDC DC contactor, 2 N/O, 2 NC, 1000 V: 400 A, RDS 250: 110 - 250 V 40 - 60 Hz/110 - 350 V DC, AC and DC operation

DC contactor, device for world markets: UL/CSA, CCC, compact dimensions, comfort series with the option of being directly actuated via PLC, with integrated suppressor circuit in the actuation electronics, conforms to IEC/EN 60947, with AC/DC wide-voltage-range coil, electronically controlled, minimized pick-up and hold-in power, enhanced electromagnetic compatibility, control cable connections with screw terminals, 2 N/O 2 N/C auxiliary contacts installed, safe isolation as per EN 61140, interlocked opposing contacts, screw fixing, can be used for up to 1000 V, IP00 degree of protection, finger-safe with terminal cover as per EN 50274, mechanical life of 1 million switching operations, available accessories: side-mounting auxiliary contact module

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors more than 170 A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILDC DC Contactor Catalog Number 186872 Model Code DILDC400/22(RDS250)

EAN 4015081819232 Product Length/Depth 248 mm Product Height 219 mm Product Width 160 mm Product Weight 7.5 kg

Certifications CSA File No.: 012528

UL508

IEC/EN 60947-5-1

CSA

UL Category Control No.: NRNT

CSA Class No.: C321124

CE

IEC/EN 60947-4-1

UL File No.: E338590

CSA-C22.2 No. 14-05

UL Catalog Notes DILDC contactors feature an electronic arc suppression system. Because of this, it is important not to exceed any technical data limits in general - especially the making and breaking capacity limits. Opening the device will immediately void the warranty. Global

Accessories Fitting options auxiliary contacts: on the side: 2 x DILM820-XHI11(V)-SI; 2 x DILM820-XHI11-SA Application DC contactor Degree of protection IP00 Electromagnetic compatibility Designed for operation in industrial environments. Its use in residential environments may cause radio-frequency interference, requiring additional noise suppression. Lifespan, mechanical 1,000,000 Operations (AC operated)

1,000,000 Operations (DC operated) Operating frequency 100 electrical Operations/h

1000 mechanical Operations/h (AC operated)

1000 mechanical Operations/h (DC operated) Overvoltage category III Pollution degree 3 Product category Contactors

Protection Finger and back-of-hand proof with terminal shroud or terminal block, Protection against direct contact when actuated from front (EN 50274...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILDC400/22(RDS250) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.