

INDUSTRIAL COMPONENT DATA

**DILER-22(190V50HZ,220V60HZ) 051775 XTRM10A22G EATON
ELECTRIC Contactor, 3-pole + 1 N/C, 3 kW/400 V/AC3**

Brand: EATON - MOELLER | Manufacturer Part Number: DILER-22(190V50HZ,220V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILER-22(190V50HZ,220V60HZ)
Catalog number	XTRM10A22G
Category	Contactor relay
Minimum order	1 Pcs
Document ID	EO-0DB7BD01D0
Generated	2026-08-06

Product Overview

Contactor, 3-pole + 1 N/C, 3 kW/400 V/AC3

Auxiliary Mini-Contactor Screw Connection 2 NO + 2 NC 190 V 50 Hz,

Contactor relay, 190 V 50 Hz, 220 V 60 Hz, N/O = Normally open: 2 N/O, N/C = Normally closed: 2 NC, Screw terminals, AC operation

Contactor relay, Product range: DILER Mini-contactors, Application: Contactor relays, Description: with interlocked opposing contacts, Connection technique: Screw terminals, Rated operational current Conventional free air thermal current, 1 pole Open at 50 °C: I_{th} = I_e = 10 A, Rated operational current AC-15 220 V 230 V 240 V: I_e = 6 A, 380 V 400 V 415 V: I_e = 3 A, Contacts N/O = Normally open: 2 N/O, Contacts N/C = Normally closed: 2 NC, Code number and version of combination Distinctive number: 22E, For use with: ...DILE, Actuating voltage: 190 V 50 Hz, 220 V 60 Hz, Voltage AC/DC: AC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

Contactor relay, 190 V 50 Hz, 220 V 60 Hz, N/O = Normally open: 2 N/O, N/C = Normally closed: 2 NC, Screw terminals, AC operation

Contactor relay, Product range: DILER Mini-contactors, Application: Contactor relays, Description: with interlocked opposing contacts, Connection technique: Screw terminals, Rated operational current Conventional free air thermal current, 1 pole Open at 50 °C: I_{th} = I_e = 10 A, Rated operational current AC-15 220 V 230 V 240 V: I_e = 6 A, 380 V 400 V 415 V: I_e = 3 A, Contacts N/O = Normally open: 2 N/O, Contacts N/C = Normally closed: 2 NC, Code number and

version of combination Distinctive number: 22E, For use with: ...DILE, Actuating voltage: 190 V 50 Hz, 220 V 60 Hz, Voltage AC/DC: AC operation, Degree of Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA Delivery program

Product range DILER Mini-contactors Application Contactor relays Description with interlocked opposing contacts Connection technique Screw terminals Rated operational current Conventional free air thermal current, 1 pole Open at 50 °C [I_{th}=I_e] 10 AAC-15 220 V 230 V 240 V [I_e] 6 AAC-15 380 V 400 V 415 V [I_e] 3 A Contacts N/O = Normally open 2 N/ON/C = Normally closed 2 NC Contact sequence Code number and version of combination Distinctive number 22E For use with... DILE Actuating voltage 190 V 50 Hz, 220 V 60 Hz Voltage AC/DC AC operation Instructions Contact numbers to EN 50011 Coil terminal markings to EN 50005 Technic...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILER-22(190V50HZ,220V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.