

INDUSTRIAL COMPONENT DATA

DILER-31(600V60HZ) 010093 XTRM10A31K6 EATON ELECTRIC AC contactor relay 3 NO / 1 NC

Brand: EATON - MOELLER | Manufacturer Part Number: DILER-31(600V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILER-31(600V60HZ)
Catalog number	XTRM10A31K6
Category	Contactor relay
Minimum order	1 Pcs
Document ID	EO-39FF5268E8
Generated	2026-08-06

Product Overview

AC contactor relay 3 NO / 1 NC

Mini-Contactor Auxiliary; Connection screw; 3 NO + 1 NC; 600 V 60 Hz

Contactor relay, 600 V 60 Hz, N/O = Normally open: 3 N/O, N/C = Normally closed: 1 NC, Screw terminals, AC operation
Contactor relay, Product range: DILER Mini-contactors, Application: Contactor relays, Description: with interlocked opposing contacts, Connection technique: Screw terminals, Rated operational current Conventional free air thermal current, 1 pole
Open at 50 °C: I_{th} = I_e = 10 A, Rated operational current AC-15 220 V 230 V 240 V: I_e = 6 A, 380 V 400 V 415 V: I_e = 3 A,
Contacts N/O = Normally open: 3 N/O, Contacts N/C = Normally closed: 1 NC, Code number and version of combination
Distinctive number: 31E, For use with: ...DILE, Actuating voltage: 600 V 60 Hz, Voltage AC/DC: AC operation, Degree of
Protection: IP20 , Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, Standards: IEC/EN
60947, EN 60947-5-1, VDE 0660, UL, CSA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

Contactor relay, 600 V 60 Hz, N/O = Normally open: 3 N/O, N/C = Normally closed: 1 NC, Screw terminals, AC
operation Contactor relay, Product range: DILER Mini-contactors, Application: Contactor relays, Description: with interlocked
opposing contacts, Connection technique: Screw terminals, Rated operational current Conventional free air thermal current,
1 pole Open at 50 °C: I_{th} = I_e = 10 A, Rated operational current AC-15 220 V 230 V 240 V: I_e = 6 A, 380 V 400 V 415 V: I_e = 3
A, Contacts N/O = Normally open: 3 N/O, Contacts N/C = Normally closed: 1 NC, Code number and version of combination
Distinctive number: 31E, For use with: ...DILE, Actuating voltage: 600 V 60 Hz, Voltage AC/DC: AC operation, Degree of

Protection: IP20, Instructions: Contact numbers to EN 50011, Coil terminal markings to EN 50005, Standards: IEC/EN 60947, EN 60947-5-1, VDE 0660, UL, CSA Delivery program

Product range DILER Mini-contactors Application Contactor relays Description with interlocked opposing contacts Connection technique Screw terminals Rated operational current Conventional free air thermal current, 1 pole Open at 50 °C [$I_{th}=I_e$] 10 AAC-15220 V 230 V 240 V [I_e] 6 AAC-15380 V 400 V 415 V [I_e] 3 A Contacts N/O = Normally open 3 N/ON/C = Normally closed 1 NC Contact sequence Code number and version of combination Distinctive number 31E For use with... DILE Actuating voltage 600 V 60 Hz Voltage AC/DC AC operation Instructions Contact numbers to EN 50011

Coil terminal markings to EN 50005 Technical data

General Standards IEC/EN 60947, E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILER-31(600V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.