

INDUSTRIAL COMPONENT DATA

DILK12-11(24V50HZ) 293967 Y7-293967 EATON ELECTRIC

Contact for Capacitors 3 Pole 12.5 kVAR 24 V 50 Hz

Brand: EATON - MOELLER | Manufacturer Part Number: DILK12-11(24V50HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILK12-11(24V50HZ)
Catalog number	Y7-293967
Category	Capacitor contactor
Minimum order	1 Pcs
Document ID	EO-9BED5071B3
Generated	2026-08-06

Product Overview

Contactor for Capacitors; 3 Pole; 12.5 kVAR; 24 V 50 Hz

DILK12-11(24V50HZ)

Eaton Moeller® series DILK Contactor for capacitors, with series resistors, 12.5 kVAr, 24 V 50 Hz

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILK capacity contactor Catalog Number 293967 Model Code DILK12-11(24V50HZ)
EAN 4015082939670 Product Length/Depth 138 mm Product Height 135 mm Product Width 45 mm Product Weight 0.61 kg
Certifications IEC/EN 60947

VDE 0660 Features & Functions

Fitted with: Series resistors General

Application Contactors for power factor correction Lifespan, electrical 150,000 Operations Operating frequency 120
Operations/h Product category DILK Contactors for capacitors Protection Finger and back-of-hand proof, Protection against
direct contact when actuated from front (EN 50274) Voltage type AC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Ambient operating temperature
(enclosed) - min 25 °C Ambient operating temperature (enclosed) - max 40 °C Electro Magnetic Compatibility

Emitted interference According to EN 60947-1 Interference immunity According to EN 60947-1 Terminal capacities

Terminal capacity (flexible with ferrule) 1 x (0.75 - 16) mm², Main cables Terminal capacity (solid) 1 x (0.75 - 16) mm², Main

cables Terminal capacity (solid/stranded AWG) 18 - 6, Main cables Terminal capacity (stranded) 1 x 16 mm², Main cables Electrical Rating

Rated operational current (I_e) 18 A at 525 V (three-phase capacitors, open)

18 A at 690 V (three-phase capacitors, open)

16 A at 690 V (three-phase capacitors, enclosed)

16 A at 230 V (three-phase capacitors, enclosed)

18 A...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILK12-11(24V50HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.