


**INDUSTRIAL COMPONENT DATA**

# DILM12-XRA2 239372 Y7-239372 EATON ELECTRIC Reversing bridge, for DILM7-15

Brand: EATON - MOELLER | Manufacturer Part Number: DILM12-XRA2



|                 |                                                           |
|-----------------|-----------------------------------------------------------|
| Manufacturer    | EATON - MOELLER                                           |
| MPN / Reference | DILM12-XRA2                                               |
| Catalog number  | Y7-239372                                                 |
| Category        | Accessories/spare parts for low-voltage switch technology |
| Minimum order   | 20 Pcs                                                    |
| Document ID     | EO-7B30579006                                             |
| Generated       | 2026-08-03                                                |

## Product Overview

Reversing bridge, for DILM7-15

DILM12-XRA2

Eaton Moeller® series DILM Reversing bridge, for DILM7-M12 DILM12-XRA2

Plug-in main current wiring bridge for quick, simple mounting

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **EATON - MOELLER > Contactors up to 170A**

## Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM reversing bridge Catalog Number 239372 Model Code DILM12-XRA2 EAN 4015082393724 Product Length/Depth 30 mm Product Height 6.8 mm Product Width 90 mm Product Weight 0.014 kg

Certifications CSA File No.: 012528

UL File No.: E36332

UL 508

CSA

CSA-C22.2 No. 14-05

UL Category Control No.: NLRV

CE

UL

IEC/EN 60947-4-1

CSA Class No.: 3211-05 General

Accessory/spare part type Connecting bridge Product category Accessories Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Design verification

Equipment heat dissipation, current-dependent P<sub>vid</sub> 2.1 W Heat dissipation capacity P<sub>diss</sub> 0 W Rated operational current

for specified heat dissipation (I<sub>n</sub>) 22 A 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance

of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal

heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements. 10.2.5 Lifting Does not apply, since the entire switchgear needs to be

evaluated. 10.2.6 Mechanical impact Does not apply, since the entire switchgear needs to be evaluated. 10.2.7 Inscriptions

Meets the product sta...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM12-XRA2 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.