

INDUSTRIAL COMPONENT DATA

DILM150-22(RAC120) 239597 Y7-239597 EATON ELECTRIC Contactor, 3p+2N/O+2N/C, 75kW/400V/AC3

Brand: EATON - MOELLER | Manufacturer Part Number: DILM150-22(RAC120)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM150-22(RAC120)
Catalog number	Y7-239597
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-A3B79EC6DB
Generated	2026-08-06

Product Overview

Contactor, 3p+2N/O+2N/C, 75kW/400V/AC3

DILM150-22(RAC120)

Eaton Moeller® series DILM Contactor, 380 V 400 V 75 kW, 2 N/O, 2 NC, RAC 120: 110 - 120 V 50/60 Hz, AC operation, Screw terminals

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM contactor Catalog Number 239597 Model Code DILM150-22(RAC120) EAN 4015082395971 Product Length/Depth 175 mm Product Height 170 mm Product Width 90 mm Product Weight 2.31 kg

Certifications IEC/EN 60947-4-1

UL

IEC/EN 60947

VDE 0660

CSA File No.: 012528

UL File No.: E29096

UL 508

CE

UL Category Control No.: NLDX

CSA-C22.2 No. 14-05

CSA Class No.: 2411-03, 3211-04

CSA Catalog Notes Contacts according to EN 50012 Features & Functions

Fitted with: Mirror contact

Suppressor circuit in actuating electronics Number Of Poles Three-pole General

Application Contactors for Motors Lifespan, mechanical 10,000,000 Operations (AC operated) Operating frequency 3600 mechanical Operations/h (AC operated) Overvoltage category III Pollution degree 3 Product category Contactors Protection

Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 8000 V AC Residual current 1 mA (with actuation of A1 - A2 by the electronics with "0" signal)

Resistance per pole 0.6 m Ω Suitable for Also motors with efficiency class IE3 Utilization category AC-4: Normal AC

induction motors: starting, plugging, reversing, inching

AC-1: Non-inductive or slightly inductive loads, resistance furnaces

AC-3: Normal AC induction motors: starting, switch off during running Voltage type AC Ambient conditions, mechanical

Shock resistance 7 g, N/O auxiliary contact, Mechanical, according...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM150-22(RAC120) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.