

**INDUSTRIAL COMPONENT DATA**

# DILM225A-XSP(RAC24) 139562 Y7-139562 EATON ELECTRIC

## Coil spare AC For DILM185A / 225A RAC24

Brand: EATON - MOELLER | Manufacturer Part Number: DILM225A-XSP(RAC24)



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | EATON - MOELLER     |
| MPN / Reference | DILM225A-XSP(RAC24) |
| Catalog number  | Y7-139562           |
| Category        | Coil for relay      |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-8D4E7BDC83       |
| Generated       | 2026-08-06          |

### Product Overview

Coil spare AC; For DILM185A / 225A; RAC24

DILM225A-XSP(RAC24)

Eaton Moeller® series DILM Replacement coil, Tool-less plug connection, RAC 24: 24 V 50/60 Hz, AC, For use with: DILM185A, DILM225A

Replacement coil, Connection technique: Tool-less plug connection, Actuating voltage: RAC 24: 24 V 50/60 Hz, Voltage AC/DC: AC, For use with: DILM185A, DILM225A, DILM185A - DILM225A (incl. electronic module)

**STRUCTURED PRODUCT DATA**

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path **EATON - MOELLER > Contactors more than 170 A**

### Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM replacement coil Catalog Number 139562 Model Code DILM225A-XSP(RAC24)

EAN 4015081363407 Product Length/Depth 95 mm Product Height 48 mm Product Width 92 mm Product Weight 0.34 kg

Certifications IEC/EN 60947-4-1

UL 60947-4-1

UL Category Control No.: NLDX

CSA File No.: 2389068

CSA-C22.2 No. 60947-4-1-14

CSA Class No.: 3211-04

CE

UL File No.: E29096

CSA

UL Global

Accessories Individual coils Product category Accessories General

Ambient operating temperature - min -40 °C Ambient operating temperature - max 60 °C Product category Accessories

Switching capacity

Rated control supply voltage (Us) at AC, 50 Hz - min 24 V Rated control supply voltage (Us) at AC, 50 Hz - max 24 V Rated

control supply voltage (Us) at AC, 60 Hz - min 24 V Rated control supply voltage (Us) at AC, 60 Hz - max 24 V Rated

control supply voltage (Us) at DC - min 0 V Rated control supply voltage (Us) at DC - max 0 V Magnet system

Rated control supply voltage (Us) at AC, 50 Hz - min 24 V Rated control supply voltage (Us) at AC, 50 Hz - max 24 V Rated

control supply voltage (Us) at AC, 60 Hz - min 24 V Rated control supply voltage (Us) at AC, 60 Hz - max 24 V Rated

control supply voltage (Us) at DC - min 0 V Rated control supply voltage (Us) at DC - max 0 V Contacts

10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of

enclosures Meets the product standard's requirements. 10.2.3.2 Verific...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM225A-XSP(RAC24) with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.