

INDUSTRIAL COMPONENT DATA

DILM225A-XSP(RDC24) 139568 Y7-139568 EATON ELECTRIC Coil replacement DC For DILM185A / 225A RDC24

Brand: EATON - MOELLER | Manufacturer Part Number: DILM225A-XSP(RDC24)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM225A-XSP(RDC24)
Catalog number	Y7-139568
Category	Coil for relay
Minimum order	1 Pcs
Document ID	EO-9535389CB2
Generated	2026-08-05

Product Overview

Coil replacement DC; For DILM185A / 225A; RDC24

DILM225A-XSP(RDC24)

Eaton Moeller® series DILM Replacement coil, Tool-less plug connection, RDC 24: 24 - 27 V DC, DC, For use with: DILM185A, DILM225A

Replacement coil, Connection technique: Tool-less plug connection, Actuating voltage: RDC 24: 24 - 27 V DC, Voltage AC/DC: DC, For use with: DILM185A, DILM225A, DILM185A - DILM225A (incl. electronic module)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors more than 170 A
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM replacement coil Catalog Number 139568 Model Code

DILM225A-XSP(RDC24) EAN 4015081363469 Product Length/Depth 95 mm Product Height 48 mm Product Width 92 mm

Product Weight 0.34 kg Certifications CE

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947-4-1

UL 60947-4-1

CSA

CSA File No.: 2389068

UL Category Control No.: NLDX

CSA Class No.: 3211-04

UL

UL File No.: E29096 Global

Accessories Individual coils Product category Accessories General

Ambient operating temperature - min -40 °C Ambient operating temperature - max 60 °C Product category Accessories

Switching capacity

Rated control supply voltage (Us) at AC, 50 Hz - min 0 V Rated control supply voltage (Us) at AC, 50 Hz - max 0 V Rated control supply voltage (Us) at AC, 60 Hz - min 0 V Rated control supply voltage (Us) at AC, 60 Hz - max 0 V Rated control supply voltage (Us) at DC - min 24 V Rated control supply voltage (Us) at DC - max 27 V Magnet system

Rated control supply voltage (Us) at AC, 50 Hz - min 0 V Rated control supply voltage (Us) at AC, 50 Hz - max 0 V Rated control supply voltage (Us) at AC, 60 Hz - min 0 V Rated control supply voltage (Us) at AC, 60 Hz - max 0 V Rated control supply voltage (Us) at DC - min 24 V Rated control supply voltage (Us) at DC - max 27 V Contacts

10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verificatio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM225A-XSP(RDC24) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.