

INDUSTRIAL COMPONENT DATA

DILM225A-XSP(RDC60) 139569 Y7-139569 EATON ELECTRIC Coil replacement DC For DILM185A / 225A RDC60

Brand: EATON - MOELLER | Manufacturer Part Number: DILM225A-XSP(RDC60)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM225A-XSP(RDC60)
Catalog number	Y7-139569
Category	Coil for relay
Minimum order	1 Pcs
Document ID	EO-8765C6E21B
Generated	2026-08-04

Product Overview

Coil replacement DC; For DILM185A / 225A; RDC60

DILM225A-XSP(RDC60)

Eaton Moeller® series DILM Replacement coil, Tool-less plug connection, RDC 60: 48 - 60 V DC, DC, For use with: DILM185A, DILM225A

Replacement coil, Connection technique: Tool-less plug connection, Actuating voltage: RDC 60: 48 - 60 V DC, Voltage AC/DC: DC, For use with: DILM185A, DILM225A, DILM185A - DILM225A (incl. electronic module)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors more than 170 A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM replacement coil Catalog Number 139569 Model Code

DILM225A-XSP(RDC60) EAN 4015081363476 Product Length/Depth 95 mm Product Height 48 mm Product Width 92 mm

Product Weight 0.34 kg Certifications UL 60947-4-1

UL Category Control No.: NLDX

UL File No.: E29096

CE

CSA File No.: 2389068

CSA

CSA Class No.: 3211-04

IEC/EN 60947-4-1

UL

CSA-C22.2 No. 60947-4-1-14 General

Accessories Individual coils Product category Accessories Voltage type DC Climatic environmental conditions

Ambient operating temperature - min -40 °C Ambient operating temperature - max 60 °C Magnet system

Rated control supply voltage (Us) at AC, 50 Hz - min 0 V Rated control supply voltage (Us) at AC, 50 Hz - max 0 V Rated control supply voltage (Us) at AC, 60 Hz - min 0 V Rated control supply voltage (Us) at AC, 60 Hz - max 0 V Rated control supply voltage (Us) at DC - min 48 V Rated control supply voltage (Us) at DC - max 60 V Design verification

10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.5 Lifting Does not apply, since the entire switchgear needs to be evaluated. 10.2.6 Mechanical im...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM225A-XSP(RDC60) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.