

INDUSTRIAL COMPONENT DATA

DILM25-21(RDC24) 277210 Y7-277210 EATON ELECTRIC Contactor, 3p+2N/O+1N/C, 11kW/400V/AC3

Brand: EATON - MOELLER | Manufacturer Part Number: DILM25-21(RDC24)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM25-21(RDC24)
Catalog number	Y7-277210
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-F048AB5444
Generated	2026-08-05

Product Overview

Contactor, 3p+2N/O+1N/C, 11kW/400V/AC3

DILM25-21(RDC24)

Contactor, 380 V 400 V 11 kW, 2 N/O, 1 NC, RDC 24: 24 - 27 V DC, DC operation, Screw terminals

Contactor, Application: Contactors for Motors, Complete devices up to 170 A, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Rated operational current AC-3 380 V 400 V: I_e= 25 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th} = I_e = 45 A, enclosed: I_{th} = 36 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: I_{th} = 100 A, enclosed: I_{th} = 90 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P = 7.5 kW, 380 V 400 V: P = 11 kW, 660 V 690 V: P = 14 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P = 3.5 kW, 380 V 400 V: P = 6 kW, 660 V 690 V: P = 8.5 kW, Contacts N/O = Normally open: 2 N/O, Contacts N/C = Normally closed: 1 NC, Instructions: Contacts to EN 50 012., integrated suppressor circuit in actuating electronics, with mirror contact., Voltage AC/DC: DC oper...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

Contactor, 380 V 400 V 11 kW, 2 N/O, 1 NC, RDC 24: 24 - 27 V DC, DC operation, Screw terminals
Contactor, Application: Contactors for Motors, Complete devices up to 170 A, Utilization category: AC-1: Non-inductive or slightly inductive loads,

resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Rated operational current AC-3 380 V 400 V: I_e= 25 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole , 50 - 60 Hz Open at 40 °C: I_{th}=I_e= 45 A, enclosed: I_{th}= 36 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: I_{th}= 100 A, enclosed: I_{th}= 90 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P= 7.5 kW, 380 V 400 V: P= 11 kW, 660 V 690 V: P= 14 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P= 3.5 kW, 380 V 400 V: P= 6 kW, 660 V 690 V: P= 8.5 kW, Contacts N/O = Normally open: 2 N/O, Contacts N/C = Normally closed: 1 NC, Instructions: Contacts to EN 50 012., integrated suppressor circuit in actuating electronics, with mirror contact., Voltage AC/DC: DC operation

General specificationsProduct nameEaton Moeller® series DILM contactorPart
no.DILM25-21(RDC24)EAN4015082772109Product Length/Depth138 millimetreProduct...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM25-21(RDC24) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.