

INDUSTRIAL COMPONENT DATA

DILM32-XP2 239371 Y7-239371 EATON ELECTRIC Parallel connection For DILM17...32

Brand: EATON - MOELLER | Manufacturer Part Number: DILM32-XP2



Manufacturer	EATON - MOELLER
MPN / Reference	DILM32-XP2
Catalog number	Y7-239371
Category	Accessories/spare parts for low-voltage switch technology
Minimum order	20 Pcs
Document ID	EO-BE4AF14406
Generated	2026-08-03

Product Overview

Parallel connection; For DILM17...32

DILM32-XP2

Eaton Moeller® series DILM Paralleling link, for DILM17-M32

Quick, reliable wiring using finished, three-pole wire jumpers.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Contactors up to 170A**

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM paralleling link Catalog Number 239371 Model Code DILM32-XP2 EAN 4015082393717 Product Length/Depth 29 mm Product Height 26 mm Product Width 81 mm Product Weight 0.029 kg

Certifications CSA File No.: 012528

UL 508

CSA Class No.: 3211-04

UL

CSA

UL Category Control No.: NLRV

UL File No.: E36332

CE

CSA-C22.2 No. 14-05

IEC/EN 60947-4-1 General

Accessory/spare part type Connecting bridge Product category Accessories Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Short-circuit rating

Short-circuit current rating (basic rating) 125 A, max. CB, SCCR (UL/CSA)

5 kA, SCCR (UL/CSA)

125 A, max. Fuse, SCCR (UL/CSA) Short-circuit current rating (high fault at 480 V) 10/100 kA, Fuse, SCCR (UL/CSA)

50/32 A, max. CB, SCCR (UL/CSA)

125/70 A, Class J, max. Fuse, SCCR (UL/CSA)

10/65 kA, CB, SCCR (UL/CSA) Short-circuit current rating (high fault at 600 V) 50/32 A, max. CB, SCCR (UL/CSA)

10/100 kA, Fuse, SCCR (UL/CSA)

125/125 A, Class J, max. Fuse, SCCR (UL/CSA)

10/22 kA, CB, SCCR (UL/CSA) Design verification

Equipment heat dissipation, current-dependent P_{vid} 1.8 W Heat dissipation capacity P_{diss} 0 W Rated operational current

for specified heat dissipation (I_n) 45 A 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resist...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM32-XP2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.