


INDUSTRIAL COMPONENT DATA

**DILM7-10(380V50HZ,440V60HZ) 276551 Y7-276551 EATON
ELECTRIC Power Contactor 3-pole + 1 NO 3 kW / 400 V / AC3..**

Brand: EATON - MOELLER | Manufacturer Part Number: DILM7-10(380V50HZ,440V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM7-10(380V50HZ,440V60HZ)
Catalog number	Y7-276551
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-144DA15C48
Generated	2026-08-06

Product Overview

Power Contactor; 3-pole + 1 NO; 3 kW / 400 V / AC3; 380 V 50 HZ, 440 V, 60HZ

DILM7-10(380V50HZ,440V60HZ)

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 3 kW, 1 N/O, 380 V 50 Hz, 440 V 60 Hz, AC operation, Screw terminals

Contactor, Application: Contactors for Motors, Contactors up to 170 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: I_{le} = 7 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th} = I_{le} = 22 A, enclosed: I_{th} = 18 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: I_{th} = 50 A, enclosed: I_{th} = 45 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P = 2.2 kW, 380 V 400 V: P = 3 kW, 660 V 690 V: P = 3.5 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P = 1 kW, 380 V 400 V: P = 2.2 kW, 660 V 690 V: P = 2.9 kW, Can be combined with auxiliary contact: DILM32-XHI., DILA-XHI(V).., Contacts N/O = Normally open: 1 N/O, I...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM contactor Catalog Number 276551 Model Code

DILM7-10(380V50HZ,440V60HZ) EAN 4015082765514 Product Length/Depth 75 mm Product Height 68 mm Product Width 45 mm Product Weight 0.24 kg Compliances CE Marked Certifications IEC 60947-4-1

UL 508

EN 60947-4-1

CSA Std. C22.2 No. 14-05

VDE

CSA File No.: 012528

CSA

CSA Class No.: 2411-03, 3211-04

UL

CSA-C22.2 No. 60947-4-1-14

UL 60947-4-1

UL File No.: E29096

CE

IEC/EN 60947-4-1

IEC/EN 60947

VDE 0660

UL Category Control No.: NLDX Catalog Notes Contacts according to EN 50012 Product specifications

Electrical connection type for auxiliary- and control-current circuit Screw connection Amperage Rating 7A Number Of Poles

Three-pole Voltage rating 380-440 V 10.10 Temperature rise The panel builder is responsible for the temperature rise

calculation. Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's

responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel

builder's responsibility. The specifications for the switchgear must be observed. 10.13 Mechanical function The device

meets the requirements, provided the information in the instruction leaflet (IL) is observed. 10.2.2 Corrosion resistance

Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product

standard's requirements. 10.2.3.2 Verification of resist...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM7-10(380V50HZ,440V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.