

INDUSTRIAL COMPONENT DATA

DILM7-32(24VDC) 276670 Y7-276670 EATON ELECTRIC Contactor, 3p+3N/O+2N/C, 3kW/400V/AC3

Brand: EATON - MOELLER | Manufacturer Part Number: DILM7-32(24VDC)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM7-32(24VDC)
Catalog number	Y7-276670
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-478AF9B4DE
Generated	2026-08-05

Product Overview

Contactor, 3p+3N/O+2N/C, 3kW/400V/AC3

DILM7-32(24VDC)

Eaton Moeller® series DILM Contactor, 380 V 400 V 3 kW, 3 N/O, 2 NC, 24 V DC, DC operation, Screw terminals

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM contactor Catalog Number 276670 Model Code DILM7-32(24VDC) EAN

4015082766702 Product Length/Depth 117 mm Product Height 68 mm Product Width 45 mm Product Weight 0.354 kg

Certifications CSA Class No.: 2411-03, 3211-04

IEC/EN 60947

CSA-C22.2 No. 60947-4-1-14

UL File No.: E29096

UL

CSA

IEC/EN 60947-4-1

UL 60947-4-1

UL Category Control No.: NLDX

VDE 0660

CE

CSA File No.: 012528 Catalog Notes Contacts according to EN 50012 Features & Functions

Fitted with: Mirror contact

Varistor suppressor circuit Number Of Poles Three-pole General

Application Contactors for Motors Lifespan, mechanical 10,000,000 Operations (DC operated)

7,000,000 Operations (Coil 50/60 Hz) Operating frequency 5000 mechanical Operations/h (DC operated) Overvoltage category III Pollution degree 3 Product category Contactors Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 8000 V AC Resistance per pole 4.6 m Ω ? Suitable for Also motors with efficiency class IE3 Utilization category AC-3: Normal AC induction motors: starting, switch off during running

AC-1: Non-inductive or slightly inductive loads, resistance furnaces

AC-4: Normal AC induction motors: starting, plugging, reversing, inching Voltage type DC Ambient conditions, mechanical Shock resistance 3.4 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-si...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM7-32(24VDC) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.