

INDUSTRIAL COMPONENT DATA

DILM72(RDC240) 109209 Y7-109209 EATON ELECTRIC Power Contactor 3-pole 37 kW / 400 V / AC3 RDC240

Brand: EATON - MOELLER | Manufacturer Part Number: DILM72(RDC240)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM72(RDC240)
Catalog number	Y7-109209
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-8CC96C0F70
Generated	2026-08-06

Product Overview

Power Contactor; 3-pole; 37 kW / 400 V / AC3; RDC240

DILM72(RDC240)

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 37 kW, RDC 240: 200 - 240 V DC, DC operation, Screw terminals DILM72(RDC240)

Contactor, Application: Contactors for Motors, Contactors up to 170 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Not suitable for motors with efficiency class IE3., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: I_e= 72 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th} = I_e= 98 A, enclosed: I_{th}= 72 A , Rated operational current AC-1 Conventional free air thermal current, 1 pole open: I_{th}= 200 A, enclosed: I_{th}= 180 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P= 22 kW, 380 V 400 V: P= 37 kW, 660 V 690 V: P= 35 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P= 7 kW, 380 V 400 V: P= 12 kW, 660 V 690 V: P= 17 kW, Can be combined with auxiliary contact: DILM150-XHI(V)..., DILM1000-XHI(V)..., Instructions: Contacts to EN 50 012., integrated suppressor circuit in actuating electronics, Observe electrical lifespan., Vo...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM contactor Catalog Number 109209 Model Code DILM72(RDC240) EAN

4015081088270 Product Length/Depth 132.1 mm Product Height 115 mm Product Width 55 mm Product Weight 1.052 kg

Certifications UL

IEC/EN 60947-4-1

UL 60947-4-1

CE

VDE 0660

CSA

CSA File No.: 012528

CSA Class No.: 2411-03, 3211-04

CSA-C22.2 No. 60947-4-1-14

UL File No.: E29096

IEC/EN 60947

UL Category Control No.: NLDX Catalog Notes Contacts according to EN 50012 Product specifications

Number Of Poles Three-pole 10.10 Temperature rise The panel builder is responsible for the temperature rise calculation.

Eaton will provide heat dissipation data for the devices. 10.11 Short-circuit rating Is the panel builder's responsibility. The specifications for the switchgear must be observed. 10.12 Electromagnetic compatibility Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2

Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects Meets the product standard's requirements. 10.2.4 Resist...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM72(RDC240) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.