

INDUSTRIAL COMPONENT DATA

DILM80(240V50HZ) 235910 Y7-235910 EATON ELECTRIC Power Contactor 3-pole 37 kW / 400 V / AC3 240 V 50HZ

Brand: EATON - MOELLER | Manufacturer Part Number: DILM80(240V50HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM80(240V50HZ)
Catalog number	Y7-235910
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-6E8EA8F3AE
Generated	2026-08-06

Product Overview

Power Contactor; 3-pole; 37 kW / 400 V / AC3; 240 V 50HZ

DILM80(240V50HZ)

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 37 kW, 240 V 50 Hz, AC operation, Screw terminals

DILM80(240V50HZ)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM contactor Catalog Number 235910 Model Code DILM80(240V50HZ) EAN 4015082359102 Product Length/Depth 160 mm Product Height 170 mm Product Width 90 mm Product Weight 2.18 kg

Certifications IEC/EN 60947

CSA File No.: 012528

IEC/EN 60947-4-1

CE

UL 60947-4-1

UL File No.: E29096

CSA-C22.2 No. 60947-4-1-14

VDE 0660

UL

CSA Class No.: 2411-03, 3211-04

UL Category Control No.: NLDX

CSA Catalog Notes Contacts according to EN 50012 Features & Functions

Number Of Poles Three-pole General

Application Contactors for Motors Frame size FS4 Lifespan, mechanical 10,000,000 Operations (AC operated) Operating frequency 3600 mechanical Operations/h (AC operated) Overvoltage category III Pollution degree 3 Product category Contactors Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 8000 V AC Residual current 1 mA (with actuation of A1 - A2 by the electronics with "0" signal) Resistance per pole 0.6 m Ω Suitable for Also motors with efficiency class IE3 Utilization category AC-3: Normal AC induction motors: starting, switch off during running
AC-4: Normal AC induction motors: starting, plugging, reversing, inching
AC-1: Non-inductive or slightly inductive loads, resistance furnaces Voltage type AC Ambient conditions, mechanical Shock resistance 7 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 1...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM80(240V50HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.