

INDUSTRIAL COMPONENT DATA

DILM820-XHI11-SI-SOND692 265249 Y7-265249 EATON ELECTRIC Auxiliary contacts, 1 N/O + 1 N/C indoor installati..

Brand: EATON - MOELLER | Manufacturer Part Number: DILM820-XHI11-SI-SOND692



Manufacturer	EATON - MOELLER
MPN / Reference	DILM820-XHI11-SI-SOND692
Catalog number	Y7-265249
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-44A6982CCE
Generated	2026-08-06

Product Overview

Auxiliary contacts, 1 N/O + 1 N/C; indoor installation

DILM820-XHI11-SI-SOND692

Auxiliary contact module, 2 pole, 1 N/O, 1 NC, Screw terminals

Auxiliary contact module, with interlocked opposing contacts, Function: for standard applications, 2 pole, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, Rated operational current AC-15 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, Mounting type: Side mounted, For use with: DILM250 - DILH2600, DILDC300 - DILDC600, Type: Side-mounting auxiliary contacts, Instructions: Interlocked opposing contacts according to IEC/EN 60947-5-1 Appendix L, inside the auxiliary contact module , Auxiliary contacts used as mirror contacts according to IEC/EN 60947-4-1 Appendix F (not N/C late open)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors more than 170 A
--------------	--

Additional Product Information

Auxiliary contact module, 2 pole, 1 N/O, 1 NC, Screw terminalsAuxiliary contact module, with interlocked opposing contacts, Function: for standard applications, 2 pole, Connection technique: Screw terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, Rated operational current AC-15 380 V 400 V 415 V: Ie= 4 A, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, Mounting type: Side mounted, For use with: DILM250 - DILH2600, DILDC300 - DILDC600, Type: Side-mounting auxiliary contacts, Instructions: Interlocked opposing contacts according to IEC/EN 60947-5-1 Appendix L, inside the auxiliary contact module, Auxiliary contacts used as mirror contacts according to IEC/EN 60947-4-1 Appendix F (not N/C late open)Delivery program

AccessoriesAuxiliary contact modulesDescriptionwith interlocked opposing contactsFunctionfor standard applicationsNumber of poles2 poleConnection techniqueScrew terminalsRated operational currentConventional free air thermal current, 1 poleOpenat 60 °C [Ith]10 AAC-15220 V 230 V 240 V [Ie]4 AAC-15380 V 400 V 415 V [Ie]4 AContactsN/O = Normally open1 N/ON/C = Normally closed1 NCMounting typeSide mountedFor use withDILM250 - DILH2600 DILDC300 - DILDC600TypeSide-mounting auxiliary contactsInstructionsInterlocked opposing contacts according to IEC/EN 60947-5-1 Appendix L, inside the auxiliary contact module
Auxiliary contacts used as mirror contacts according to IEC/EN 60947-4-1 Appendix F (not N/C late open)Technical data G...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM820-XHI11-SI-SOND692 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.