

INDUSTRIAL COMPONENT DATA

DILM9-10(220V50/60HZ)-PI 199647 Y7-199647 EATON ELECTRIC DILM9-10(220V50/60HZ)-PI

Brand: EATON - MOELLER | Manufacturer Part Number: DILM9-10(220V50/60HZ)-PI



Manufacturer	EATON - MOELLER
MPN / Reference	DILM9-10(220V50/60HZ)-PI
Catalog number	Y7-199647
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-A237AA1FBB
Generated	2026-08-06

Product Overview

DILM9-10(220V50/60HZ)-PI

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 4 kW, 1 N/O, 220 V 50/60 Hz, AC operation, Push in terminals
Contactor, Application: Contactors for Motors, Contactors up to 95 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Push in terminals, Notes: Also suitable for motors with efficiency class IE3., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: I_e = 9 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th} = I_e = 22 A, enclosed: I_{th} = 18 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: I_{th} = 50 A, enclosed: I_{th} = 45 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P = 2.5 kW, 380 V 400 V: P = 4 kW, 660 V 690 V: P = 4.5 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P = 1.5 kW, 380 V 400 V: P = 2.5 kW, 660 V 690 V: P = 3.6 kW, Can be combined with auxiliary contact: DILM12-XHI...-PI, DILM32-XHI...-PI, DILA-XHI(V)...-PI, Contacts N/O = Normally open: 1 N/O, Instructions: Contacts to EN 50 012., Voltage AC/DC: AC operation

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM contactor Catalog Number 199647 Model Code DILM9-10(220V50/60HZ)-PI
EAN 4015081983483 Product Length/Depth 75 mm Product Height 68 mm Product Width 45 mm Product Weight 0.225 kg

Certifications VDE 0660

IEC/EN 60947 Features & Functions

Number Of Poles Three-pole General

Application Contactors for Motors Frame size FS1 Lifespan, mechanical 10,000,000 Operations (AC operated) Operating frequency 9000 mechanical Operations/h (AC operated) Overvoltage category III Pollution degree 3 Product category Contactors Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 6000 V AC Suitable for Also motors with efficiency class IE3 Utilization category AC-4: Normal AC induction motors: starting, plugging, reversing, inching

AC-1: Non-inductive or slightly inductive loads, resistance furnaces

AC-3: Normal AC induction motors: starting, switch off during running Voltage type AC Ambient conditions, mechanical Shock resistance 3.4 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms

5.7 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms

3.4 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10 ms

10 g, N/O main contact, Mechanical, according to...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM9-10(220V50/60HZ)-PI with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.