

INDUSTRIAL COMPONENT DATA

DILM95-22(RDC24) 239541 Y7-239541 EATON ELECTRIC Contactor, 3p+2N/O+2N/C, 45kW/400V/AC3

Brand: EATON - MOELLER | Manufacturer Part Number: DILM95-22(RDC24)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM95-22(RDC24)
Catalog number	Y7-239541
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-FEE0515E63
Generated	2026-08-05

Product Overview

Contactor, 3p+2N/O+2N/C, 45kW/400V/AC3

DILM95-22(RDC24)

Eaton Moeller® series DILM Contactor, 380 V 400 V 45 kW, 2 N/O, 2 NC, RDC 24: 24 - 27 V DC, DC operation, Screw terminals

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILM contactor Catalog Number 239541 Model Code DILM95-22(RDC24) EAN 4015082395414 Product Length/Depth 175 mm Product Height 170 mm Product Width 90 mm Product Weight 2.32 kg

Certifications CE

CSA File No.: 012528

UL

UL File No.: E29096

VDE 0660

CSA

IEC/EN 60947

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947-4-1

UL Category Control No.: NLDX

UL 60947-4-1

CSA Class No.: 2411-03, 3211-04 Catalog Notes Contacts according to EN 50012 Features & Functions

Fitted with: Mirror contact

Suppressor circuit in actuating electronics Number Of Poles Three-pole General

Application Contactors for Motors Lifespan, mechanical 10,000,000 Operations (DC operated)

7,000,000 Operations (Coil 50/60 Hz) Operating frequency 3600 mechanical Operations/h (DC operated) Overvoltage category III Pollution degree 3 Product category Contactors Protection Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) Rated impulse withstand voltage (Uimp) 8000 V AC Residual current 1 mA (with actuation of A1 - A2 by the electronics with "0" signal) Resistance per pole 0.6 m Ω ? Suitable for Also motors with efficiency class IE3 Utilization category AC-1: Non-inductive or slightly inductive loads, resistance furnaces AC-4: Normal AC induction motors: starting, plugging, reversing, inching AC-3: Normal AC induction motors: starting, switch off during running Voltage type DC Ambient conditions, mechanical Shock resistance 5...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM95-22(RDC24) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.