

INDUSTRIAL COMPONENT DATA

DILM95(TVC100) 239494 XTCE095F00E6 EATON ELECTRIC Contactor, 3p, 45kW/400V/AC3

Brand: EATON - MOELLER | Manufacturer Part Number: DILM95(TVC100)



Manufacturer	EATON - MOELLER
MPN / Reference	DILM95(TVC100)
Catalog number	XTCE095F00E6
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-27F7250751
Generated	2026-08-05

Product Overview

Contactor, 3p, 45kW/400V/AC3

Power Contactor; Connection screw; 3 pole; 95 To; 45 kW; 400 V; AC-3; TVC100

Contactor, 3 pole, 380 V 400 V 45 kW, TVC100: 100 V 50 Hz/100-110 V 60 Hz, AC operation, Screw terminals

Contactor, Application: Contactors for Motors, Contactors up to 170 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: I_e = 95 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th} = I_e = 130 A, enclosed: I_{th} = 100 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: I_{th} = 275 A, enclosed: I_{th} = 250 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P = 30 kW, 380 V 400 V: P = 45 kW, 660 V 690 V: P = 75 kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: P = 16 kW, 380 V 400 V: P = 26 kW, 660 V 690 V: P = 35 kW, Can be combined with auxiliary contact: DILM150-XHI(V)..., DILM1000-XHI(V)..., Instructions: Contacts to EN 50 012., Voltage AC...

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

Contactor, 3 pole, 380 V 400 V 45 kW, TVC100: 100 V 50 Hz/100-110 V 60 Hz, AC operation, Screw terminals
Contactor, Application: Contactors for Motors, Contactors up to 170 A, 3 pole, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal

AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: $I_e = 95$ A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: $I_{th} = I_e = 130$ A, enclosed: $I_{th} = 100$ A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: $I_{th} = 275$ A, enclosed: $I_{th} = 250$ A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: $P = 30$ kW, 380 V 400 V: $P = 45$ kW, 660 V 690 V: $P = 75$ kW, Max. rating for three-phase motors, 50 - 60 Hz AC-4 220 V 230 V: $P = 16$ kW, 380 V 400 V: $P = 26$ kW, 660 V 690 V: $P = 35$ kW, Can be combined with auxiliary contact: DILM150-XHI(V)..., DILM1000-XHI(V)..., Instructions: Contacts to EN 50 012., Voltage AC/DC: AC operation Delivery program

Product range Contactors Application Contactors for Motors Subrange Contactors up to 170 A, 3 pole Utilization category AC-1: Non-inductive or slightly inductive loads, resistance f...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILM95(TVC100) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.