

INDUSTRIAL COMPONENT DATA

DILMF11-01(RAC240) 104425 Y7-104425 EATON ELECTRIC

Timer module, 200-240VAC, 0.1-100s, on-delayed

Brand: EATON - MOELLER | Manufacturer Part Number: DILMF11-01(RAC240)



Manufacturer	EATON - MOELLER
MPN / Reference	DILMF11-01(RAC240)
Catalog number	Y7-104425
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-8F4EC5D1E1
Generated	2026-08-05

Product Overview

Timer module, 200-240VAC, 0.1-100s, on-delayed

DILMF11-01(RAC240)

Eaton Moeller® series DILMF Contactors for Semiconductor Industries acc. to SEMI F47, 380 V 400 V: 9 A, 1 NC, RAC 240: 190 - 240 V 50/60 Hz, Screw terminals

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILMF contactor for semiconductor industries Catalog Number 104425 Model Code DILMF11-01(RAC240) EAN 4015081042425 Product Length/Depth 97 mm Product Height 85 mm Product Width 45 mm

Product Weight 0.531 kg Certifications CSA File No.: 012528

UL File No.: E29096

CE

UL Category Control No.: NLDX

IEC/EN 60947-4-1

CSA-C22.2 No. 60947-4-1-14

UL 60947-4-1

UL

CSA Class No.: 2411-03, 3211-04

CSA Catalog Notes Also tested according to AC-3e. Features & Functions

Fitted with: Mirror contact

Built-in suppressor circuit Number Of Poles Three-pole Operating mode Operating mechanism adjustable from 50 Hz to 400 Hz. General

Application Contactors for Semiconductor Industries acc. to SEMI F47 Product category Contactors Resistance per pole 2.65 m Ω Suitable for SEMI F47, Magnet systems

Also motors with efficiency class IE3 Utilization category AC-3: Normal AC induction motors: starting, switch off during running

AC-1: Non-inductive or slightly inductive loads, resistance furnaces

AC-4: Normal AC induction motors: starting, plugging, reversing, inching Voltage type AC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Electro Magnetic Compatibility

Emitted interference According to EN 60947-1 Interference immunity According to EN 60947-1 Electrical Rating

Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V 20 A Rated operational current (Ie) at AC-3, 220 V, 23...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMF11-01(RAC240) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.