

INDUSTRIAL COMPONENT DATA

DILMF65(RAC240) 104469 Y7-104469 EATON ELECTRIC Timer module, 200-240VAC, 1-30s, star-delta

Brand: EATON - MOELLER | Manufacturer Part Number: DILMF65(RAC240)



Manufacturer	EATON - MOELLER
MPN / Reference	DILMF65(RAC240)
Catalog number	Y7-104469
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-326BE8CFCD
Generated	2026-08-06

Product Overview

Timer module, 200-240VAC, 1-30s, star-delta

DILMF65(RAC240)

Eaton Moeller® series DILMF Contactors for Semiconductor Industries acc. to SEMI F47, 380 V 400 V: 65 A, RAC 240: 190 - 240 V 50/60 Hz, Screw terminals

Contactor, Application: Contactors for Semiconductor Industries acc. to SEMI F47, Contactors up to 150 A with electronic actuation, Utilization category: AC-1: Non-inductive or slightly inductive loads, resistance furnaces, NAC-3: Normal AC induction motors: starting, switch off during running, AC-4: Normal AC induction motors: starting, plugging, reversing, inching, Connection technique: Screw terminals, Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging., Description: Contactors suitable for semi-conductor industry according to SEMI F47., Contactors hum-free , suitable for building services automation., Operating mechanism adjustable from 50 Hz to 400 Hz., Number of poles: 3 pole, Rated operational current AC-3 380 V 400 V: I_e = 65 A, Rated operational current AC-1 Conventional free air thermal current, 3 pole, 50 - 60 Hz Open at 40 °C: I_{th} = I_e = 98 A, enclosed: I_{th} = 72 A, Rated operational current AC-1 Conventional free air thermal current, 1 pole open: I_{th} = 200 A, enclosed: I_{th} = 180 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P = 20 kW, 380 V 400 V: P = 30 kW, 660 V 690 V:....

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series DILMF contactor for semiconductor industries Catalog Number 104469 Model Code

DILMF65(RAC240) EAN 4015081042869 Product Length/Depth 132.1 mm Product Height 115 mm Product Width 55 mm
Product Weight 1.04 kg Certifications UL File No.: E29096

IEC/EN 60947-4-1

UL 60947-4-1

CSA-C22.2 No. 60947-4-1-14

UL Category Control No.: NLDX

CSA File No.: 012528

CSA

CE

CSA Class No.: 2411-03, 3211-04

UL Catalog Notes Also tested according to AC-3e. Features & Functions

Fitted with: Built-in suppressor circuit Number Of Poles Three-pole Operating mode Operating mechanism adjustable from 50 Hz to 400 Hz. General

Application Contactors for Semiconductor Industries acc. to SEMI F47 Overvoltage category III Pollution degree 3 Product category Contactors Resistance per pole 1.86 m Ω ? Suitable for SEMI F47, Magnet systems

Also motors with efficiency class IE3 Utilization category AC-4: Normal AC induction motors: starting, plugging, reversing, inching

AC-1: Non-inductive or slightly inductive loads, resistance furnaces

AC-3: Normal AC induction motors: starting, switch off during running Voltage type AC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Ambient operating temperature

(enclosed) - min -25 °C Ambient operating temperature (enclosed) - max 40 °C Ambient storage temperature - min -40 °C

Ambient storage temperature - max 80 °C Electro Magnetic Compatibility

Emitte...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / DILMF65(RAC240) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.